

SNR-32A/16A/9A

32 / 16 / 9 Channel Network Recorder Software

Technical Specifications

		SNR-32A	SNR-16A	SNR-9A
Supported H/W	Supported Devices	Network Camera : SNC-570/550, SNP-3300A/1000A Video Encoder : SNS-400/100		
	Max. Register Device	No limit		
Performance	Max. Record Channel	32	16	9
	Recording	480 CIF	480 CIF	270 CIF
	Playback	5 Client	5 Client	5 Client
Recording	Video Codec	MPEG-4, JPEG		
	Audio Codec	ADPCM		
	Resolution	D1, Half D1, CIF		
	Quality	5 level		
	Pre/Post Recording Time	60sec / 60sec		
	Recording Mode	Continue, Schedule, MD, Event, Compound		
	Set up	Configurable frame rate for each CH (1~30(N),1~25(P)), Channel independent set up		
Component Search	Camera / Sensor / Relay	32 / 32 / 32	16 / 16 / 16	9 / 9 / 9
Storage	Search Mode	Time/Calendar, Timeline, Thumbnail		
	Space Configuration (Each Drive)	Supported		
	Space Shortage Warning	Supported		
	NAS (Network Attached Storage)	Supported (External)		
User	User Level	2		
	Local (Remote) User	Group : 1, User : No limit		
	IP Filtering (Remote user)	Supported		
S/W Status	Record, Record schedule, Storage, Live/Recording image (Instant viewer)			
Data Security Technology	Login Packet Encryption	Supported		
System	System auto recovery, Auto power-on record CPU : Intel Core2Duo E8400, RAM : 2GB above Video memory : 256MB, HDD : 250GB OS : Window XP SP2, Windows 2003 SP2 DirectX 9.0 above, Microsoft .Net Framework 2, Microsoft SQL Server 2005			