



## **ACCESS** reliability.

### Application

The Multi-Chip Module (MCM) provides the functions of an HID proximity reader on a single integrated circuit. The “Prox by HID”™ technology can be easily integrated to an existing electronic module and is able to be surface mounted to an existing PCB.

The MCM enables RFID technology to be added to a wide array of electronic devices, including alarm panels, electronic door locks, biometric readers, logical access devices and process control equipment.

### Features

- ▶ Allows OEMs to make their own HID interoperable readers, while retaining their own design aesthetics and product identity.
- ▶ Reduces development and per-unit costs by sharing existing components in the OEM module, such as LED, beeper, voltage regulator and transient suppression.
- ▶ Interoperable with all HID cards and readers.
- ▶ Offers Wiegand Data 1, Data 0, and Clock and Data output features.
- ▶ Provides output for a bi-color LED.

**The MCM Reader hardware includes the following basic features:**

- Microcontroller
- 8 MHz ceramic resonator
- 128 byte EEPROM
- FSK base-band receiver circuitry
- Antenna exciter drive circuitry
- External bicolor LED drive capability
- External beeper drive capability

**Customer Supplied Components**

Several functions are partitioned outside of the MCM Reader due to their size or power dissipation requirements, or because existing electronic modules (i.e., alarm system keypads and control panels) already incorporate these functions. The MCM User Manual includes full instructions and recommended schematics for designing and connecting these functions to the MCM Reader, including:

- Voltage regulator
- Series resonant antenna circuit
- Peak detection circuit
- Transient surge protection
- Sounder
- LED's for user feedback
- Reset circuitry

**Environmental Characteristics**

**Operating temperature range**  
-30°C to 65°C (-22°F to 150°F)

**Storage temperature range**  
-40°C to 85°C (-40°F to 185°F)

**Operating humidity range**  
5% to 95% non-condensing

**Operating vibration limit**  
.04 g<sup>2</sup>/Hz 20-2000Hz

**Operating shock limit**  
30g, 11ms, Half Sine

**Power Requirements**  
**Power Supply**  
Linear type recommended

**Operating voltage range**  
4.5VDC – 5.5VDC  
Absolute maximum  
6.0VDC  
Peak current  
<150mA

**Operating Parameters**  
**Reader LED control**  
Red & Green External  
**Input Wiegand data pulse widths**  
20µSec - 100µSec  
**Frequency of Operation**  
125 KHz +/- 1 KHz  
**Input Wiegand data interval**  
200µSec – 20mSec

**Accuracy**  
The unit will not have more than 1 misread per 10 million.

**Factory Configurable Options**  
The reader MCM will be configurable via command cards.

**Mounting Option**  
The Reader MCM is designed to be a surface-mount part. By adding mounting pads to a circuit board as per the package specification drawing (included in product documentation), the part can be attached like any other surface mount IC.

**Base Part Number:** 4025.

Specifications subject to change without notice. (Please see "How to Order" guide for a description of the options and associated part numbers).

© 2011 HID Global. All rights reserved. HID, and the HID logo are trademarks or registered trademarks of HID Global in the U.S. and/or other countries. All other trademarks, service marks, and product or service names are trademarks or registered trademarks of their respective owners. Rev. 01/2011

MKT-ePROXMCM\_DS\_EN



**ACCESS** experience.

hidglobal.com

HID Global Offices:

**Corporate North America**  
15370 Barranca Pkwy  
Irvine, CA 92618  
U.S.A.  
Tel: 1 800 237 7769  
Tel: +1 949 732 2000  
Fax: +1 949 732 2360

**Asia Pacific**  
19/F 625 King's Road  
North Point  
Island East  
Hong Kong  
Tel: +852 3160 9800  
Fax: +852 3160 4809

**Latin America**  
Circunvalación Ote. #201 B  
Despacho 2  
Col. Jardines del Moral  
Leon 37160, Gto.  
Mexico  
Tel: +52 477 779 1492  
Fax: +52 477 779 1493

**Europe, Middle East & Africa**  
Haverhill Business Park  
Phoenix Road  
Haverhill, Suffolk  
CB9 7AE  
England  
Tel: +44 1440 714 850  
Fax: +44 1440 714 840