

FARGO® DTC300

DIRECT-TO-CARD PRINTER/ENCODER

The unbelievably easy way to
print and encode plastic ID cards.



CORPORATE



EDUCATION



MEMBERSHIP

Talk to your authorized Fargo integrator about how you can use your DTC300 for applications like these:

- Access Control
- Time and Attendance
- Employee Record Storage
- Photo IDs
- Equipment Checkout
- Meal Plans
- Visitor Badges
- Membership Cards
- Season Passes
- and more...

Maximize the performance of your Fargo Card Identity System. Ask your authorized Fargo integrator about:

FARGO SECURE

- Software
- Materials
- Extended Warranties
- Visual Security™ Solutions

Specifications

Print Method:	DTC300: Dye-Sublimation / Resin Thermal Transfer DTC300M: Resin Thermal Transfer
Resolution:	300 dpi (11.8 dots/mm)
Colors:	DTC300: Up to 16.7 million / 256 shades DTC300M: Monochrome
Print Ribbon Options:	DTC300: <ul style="list-style-type: none"> • Full-color with resin black and overlay panel, YMCKO*, 250 prints • Full-color with two resin black panels and overlay panel, YMCKOK*, 200 prints • Resin black and overlay panel, KO, 500 prints • Dye-sublimation black and overlay panel, BO*, 500 prints • Resin black, 1,000 prints; green, blue, red, white, 1,000 prints; silver and gold, 500 prints DTC300M: <ul style="list-style-type: none"> • Resin black and overlay panel, KO, 500 prints • Resin black, 1,000 prints; green, blue, red, white, 1,000 prints; silver and gold, 500 prints
Print Speed:**	<ul style="list-style-type: none"> • 7 seconds per card (K)* • 12 seconds per card (KO)* • 27 seconds per card (YMCKO)* • 35 seconds per card (YMCKOK)*
Accepted Standard Card Sizes:	CR-80 (3.375"L x 2.125"W / 85.6mmL x 54mmW) CR-79 Adhesive Back (3.313"L x 2.063"W / 84.1mmL x 52.4mmW)
Print Area:	CR-80 edge-to-edge (3.37"L x 2.11"W / 85.5mmL x 53.5mmW) CR-79 (3.3"L x 2.04"W / 83.8mmL x 51.8mmW)
Accepted Card Thickness:	20 mil to 30 mil (.020" to .030" / .51mm to .76mm)
Accepted Card Types:	PVC or polyester cards with polished PVC finish; monochrome resin required for 100% polyester cards; optical memory cards with PVC finish
Input Hopper Card Capacity:	100 cards (.030" / .762mm)
Output Hopper Card Capacity:	Up to 30 cards (.030" / .762mm)
Card Cleaning:	Card cleaning roller integrated into ribbon cartridge; cleaning roller is automatically replaced with each new ribbon used
Memory:	2MB RAM
Display:	Easy-to-read, backlit LCD Control Panel
Software Drivers:	Windows® 98SE/Me/2000/XP/2003
Interface:	USB 1.1 (USB 2.0 compatible)
Operating Temperature:	65° to 80° F / 18° to 27° C
Humidity:	20-80% non-condensing
Dimensions:	7.9"H x 13.62"W x 8.14"D / 201mmH x 346mmW x 207mmD (single-sided printer) 7.9"H x 18.28"W x 8.14"D / 201mmH x 464mmW x 207mmD (with dual-sided and/or e-card encoding module)
Weight:	Single-Sided: 8 lbs. / 3.63 kg Dual-Sided: 11.55 lbs. / 5.22 kg
Agency Listings:	Safety: UL 60950-1, CSA C22.2 (60950-1), and CE EMC: FCC Class A, CRC c1374, CE (EN 55022 Class A, EN 55024)
Supply Voltage:	100-240 VAC, 3.3 A
Supply Frequency:	50 Hz / 60 Hz
Warranty:	Printer – Two years; optional Extended Warranty Program (U.S. only) Printhead – Two years, unlimited pass with UltraCard™ Cards
Fargo Certified Supplies:	Fargo Card Printer/Encoders require highly specialized media to function properly. To maximize printed card quality and durability, printhead life and printer/encoder reliability, use only Fargo Certified Supplies. Fargo warranties are void, where not prohibited by law, when non-Fargo Certified Supplies are used.
Encoding Options:	Field-upgradeable: <ul style="list-style-type: none"> • ISO Magnetic Stripe Encoding, dual high- and low-coercivity, Tracks 1, 2, and 3 Factory order only: <ul style="list-style-type: none"> • Contact Smart Card Docking Station • Contactless Smart Card Encoder (HID® iCLASS™ MIFARE® and MIFARE DESFire) • Contact Smart Card Encoder reads from and writes to all ISO7816-1/2/3/4 memory and microprocessor smart cards (T=0, T=1) as well as synchronous cards • Prox Card Encoder (HID read-only)
Options:	<ul style="list-style-type: none"> • Dual-sided Printing - Factory order only • Printer Cleaning Kit • 100-card Output Hopper with/without Reject Tray
Software:	Yes: Card identity software with database



*Indicates the ribbon type and the number of ribbon panels printed where Y=Yellow, M=Magenta, C=Cyan, K=Resin Black, B=Dye-sublimation Black, O=Overlay

**Print speed indicates an approximate print speed and is measured from the time a card feeds into the printer to the time it ejects from the printer. Print speeds do not include encoding time or the time needed for the PC to process the image. Process time is dependent on the size of the file, the CPU, amount of RAM and the amount of available resources at the time of the print.

The Fargo DTC300 Card Printer/Encoder has been tested to ensure that it meets Microsoft® standards for Windows® compatibility.

Microsoft, Windows, and the Windows logo are trademarks, or registered trademarks of Microsoft Corporation in the United States and/or other countries.

FARGO®

The World's Most Secure
Card Identity Systems

6533 Flying Cloud Drive
Minneapolis, MN 55344 USA
(952) 941-9470
800-459-5636
Fax: (952) 941-7836
www.fargo.com
E-mail: sales@fargo.com

This data sheet is for informational purposes only. Fargo Electronics makes no warranties, expressed or implied, in this summary. Company and product names and data used in sample output are fictitious. Specifications are subject to change without notice. Visual Security, SmartLoad, SmartClean and SmartScreen are trademarks and Fargo and DTC are registered trademarks of Fargo Electronics, Inc. All other trademarks and registered trademarks are property of their respective companies. This is not an offer of sale.

© 2005, Fargo Electronics, Inc. All rights reserved.

REV0510