


Indala FlexISO® XT Composite Card

- ▶ **Revolutionary Composite Materials** – Resists warping caused by high-temperature application of polyester overlays by many dye-sublimation printers.
- ▶ **Ideal for High Wear-and-Tear Environments** – Such as university or factory settings.
- ▶ **Lifetime Warranty** – Although you may never need to use it, cost-effective FlexISO® XT cards are backed for life.



ACCESS choice.

Integrating HID Indala advanced FlexSecur® proximity technology within a card body, the FlexISO® XT is designed to withstand the most extreme applications. Unique composite formulation enhances the structural integrity of the card, providing additional protection of the core electronics. The FlexISO XT is particularly effective in applications that require magnetic stripe and/or barcode transactions.

The Indala FlexISO XT Card can be programmed in the factory or in the field using the Indala ProxSmith® Programmer and Toolkit with Wiegand, magnetic stripe and serial data formats. The FlexISO XT can be used interchangeably with other Indala credentials on most systems and can be ordered with specified facility codes and ID numbers.

Exclusive FlexSecur Security Technology

All HID Indala 125 kHz Proximity Cards feature FlexSecur technology which provides an added level of access system security through a verification process at the reader. A feature unique to the HID Indala product line, FlexSecur screens out unauthorized cards prior to sending card data to the host system.

This additional verification step enhances the security of your access system in two ways:

1. The entire card data field is encrypted prior to programming the card. Therefore, the data on the card cannot be decoded to determine the actual information on the card. Only the reader is able to decrypt the data and transmit it to the access control system.
2. Cards and readers can be programmed uniquely for each site, protecting the end user against unauthorized entry attempts by using cards from another facility. Again, this is unique to the HID Indala product line.

Key Features:

- ▶ ISO 7810 Compliant.
- ▶ As with all Indala cards, the FlexISO XT is compatible with all Indala readers, and can be easily encoded with the Indala ProxSmith Programmer and Toolkit.
- ▶ The passive, no-battery design allows for an infinite number of reads, and is warranted for life against defects in materials and workmanship.
- ▶ PVC Card Surface Optimized for Dye Sublimation Printing.
- ▶ Biaxially Oriented Polyester (PET) Composite Card.
- ▶ Can be combined with a magnetic stripe, bar code, a multitude of smart chips, and MIFARE®.

Features

Compatibility

Works with HID Indala 125 kHz readers. It can also be used interchangeably with other Indala credentials.

High Security

Utilizes Indala FlexSecur® technology; data encryption, 172 user definable bits, password protection, and security between card and reader.

Two Points of Authentication

The reader first authenticates the credential. After validation, the reader passes the credential's information to the host system for authentication. If the reader does not validate the credential, no information is passed on to the host system.

Rugged and Durable Design Able to Withstand Harsh Environments

The card has been able to withstand the Indala product 100k Card Bend Test without affecting the card's functionality.

Heat Resistant Cards

The printer-friendly card's front surface is compatible with both direct and re-transfer type dye-sublimation printers.

Customizable

The surface can be customized with high quality, four-color graphics, anti-counterfeiting features (UV fluorescent ink, embedded and surface holograms, and microfine printing), and personalization (variable data images).

Expanded Credential Information

Use the 172 bits to code employee's office location, grade level, department location, or any other pertinent credential information.

Convenient Card Re-Issuance

FlexISO® XT cards are backwards compatible with all Indala 125 kHz Proximity readers, allowing any number of cards to be easily re-issued, as necessary.

FlexISO® XT Card

Dimensions	3.38"H x 2.12"W x 0.03"T (86 mm x 54 mm x .76 mm) nominal		
Weight	0.20 oz (6 g)		
Typical Maximum Read Range*	Cover Design	Module	Read Range
	Linear/Arch/Curve/Wave	Slim/Wallswitch	Up to 4" (10 cm)
	Linear	Classic	Up to 5" (12 cm)
	Arch/Wave	Mid-Range	Up to 12" (30 cm)
	Arch	Long Range	Up to 26" (66 cm)
Temperature	-22° F to 158° F (-30° C to 70° C)		
Inkjet Marking	Includes sales order number and ID number matching internal ID		
Custom Graphics	Available on front and back with customer-supplied artwork		
Slot Punch	Optional vertical or horizontal (locations indicated on card)		
Coding	Wiegand, ABA Track II Magnetic Stripe, others available (exact coding standard, with no gaps or over-runs)		
Programming	Factory or field programmable via Indala ProxSmith® Programmer and Toolkit		
Part Number	FPIXT		
Description	Standard Part Number: FPIXT-SSSCNA-0000 125 kHz, white glossy finish (front), white glossy finish with Indala logo (back), inkjet marking on standard location, no slot punch, no magstripe, no artwork.		
Warranty	Lifetime		

*Dependent on local installation conditions.

Specifications are subject to change without notice.

© 2007 HID Global Corporation. All rights reserved. HID, the HID logo, Indala, FlexISO and FlexSecur are trademarks or registered trademarks of HID Global in the U.S. and/or other countries. All other trademarks, service marks, and product or service names are trademarks or registered trademarks of their respective owners. Rev. 4/2007



For best results, please print on recycled paper.

MKT-FLEXISOXT-DS-EN



ACCESS experience.

hidcorp.com

HID Global Offices:

Corporate
North America
 9292 Jeronimo Road
 Irvine, CA 92618-1905
 U.S.A.
 Phone: (800) 237-7769
 Phone: (949) 598-1600
 Fax: (949) 598-1690

Asia Pacific
 19/F 625 King's Road
 North Point
 Island East
 Hong Kong
 Phone: +852 3160-9800
 Fax: +852 3160-4809

Latin America
 Circunvalacion Ote. #201 B
 Despacho 2
 Col. Jardines del Moral
 Leon 37160, Gto.
 Mexico
 Phone: +52 477 779 1492
 Fax: +52 477 779 1493

Europe, Middle East & Africa
 Homefield Road
 Haverhill, Suffolk
 CB9 8QP
 England
 Phone: +44 (0) 1440 714 850
 Fax: +44 (0) 1440 714 840