

Insertion Wiegand Reader

Low Profile Wiegand Reader • 312



ACCESS security.

The Insertion Wiegand Reader provides in-wall mounting for a low profile installation. Unobtrusive, the Insertion Wiegand reader is ideal for office settings. A simple push in / pull out insertion of the card completes the read.

The Insertion Wiegand reader is molded of rugged, high impact plastic to resist vandals and epoxy potted to seal out moisture. It features a bi-color LED. The Insertion Wiegand reader is immune to external magnetic fields and RF signals.

For office settings and other locations that suggest an unobtrusive reader, the Insertion Wiegand reader is ideal.

Features

Mounting	Insertion readers are designed to be unobtrusive and to mount in-the-wall or to a mounting plate. The reader can be mounted with or without the reader escutcheon in place.
Visual indication	When a Wiegand card is withdrawn from the reader, the red LED flashes to green to indicate a proper read. Rejected cards are indicated with an amber color.
Indoor / outdoor design	The Insertion Wiegand reader is sealed in a rugged, potted, weatherized polymeric enclosure to withstand harsh environments and provide a high degree of vandal resistance.
Warranty	Insertion Wiegand readers are warranted against defects in materials and workmanship for life from date of shipment. (See complete warranty policy for details.)
Part Number	Base Part No.: 312
Description	Black, Bi-color LED
Options	<ul style="list-style-type: none">• Termination (6' cable or Barrier Strip)• Escutcheon (Included or Omitted)• Read Head Location (Left or Right)• Labels (Silver or Custom) <p>(Please see "How to Order" guide for a description of the options and associated part numbers.)</p>

Specifications

For use with code strip layout options:

A	right hand reader
AI	left hand reader

Input power

5-12 VDC

Current:

40mA (typical)

Dimensions:

1.18" x 3.18" x 3.0"
(3.0 x 8.1 x 7.6 cm)

Slot width:

0.062" to 0.069"
(1.6 mm to 1.75 mm)

Operating temperature:

-40° F to 160° F (-40° C to 70° C)

Operating Humidity:

10 to 95%

Weight:

10.6 oz. (301 g)

Material:

Long-wearing polymeric plastic

Certifications:

UL 294 listed
CE mark approved

Cable distance:

500 feet (150 m) using shielded 22 AWG cable

© 2007 HID Global. All rights reserved. HID, and the HID logo are trademarks or registered trademarks of HID Global in the U.S. and/or other countries. All other trademarks, service marks, and product or service names are trademarks or registered trademarks of their respective owners. Rev. 4/2007



For best results, please print on recycled paper.

MKT-INSERTION_DS_EN



ACCESS experience.

hidcorp.com

HID Global Offices:

Corporate North America
9292 Jeronimo Road
Irvine, CA 92618-1905
U.S.A.
Phone: (800) 237-7769
Phone: (949) 598-1600
Fax: (949) 598-1690

Asia Pacific
19/F 625 King's Road
North Point
Island East
Hong Kong
Phone: +852 3160-9800
Fax: +852 3160-4809

Latin America
Circunvalacion Ote. #201 B
Despacho 2
Col. Jardines del Moral
Leon 37160, Gto.
Mexico
Phone: +52 477 779 1492
Fax: +52 477 779 1493

Europe, Middle East & Africa
Homefield Road
Haverhill, Suffolk
CB9 8QP
England
Phone: +44 (0) 1440 714 850
Fax: +44 (0) 1440 714 840