

# OMNIKEY® 4321 Mobile ExpressCard™ 54

## Mobile ExpressCard™ Reader

- ▶ **Plug and Play** - Designed to facilitate easy device installation with high quality drivers\* for all major PC operating systems
- ▶ **Readily Compliant** - Meets all relevant industry standards for smooth integration in PC environment
- ▶ **Convenient and Reliable** – Robust metal housing
- ▶ **Suits Any Application** - Compatible with virtually any smart card and major PC operating systems



### ACCESS quality.

The OMNIKEY® 4321 is one of the first ExpressCard™ 54 smart card readers available on the market. The new interface standard, designed to enable smaller and faster PC card solutions for next generation PCs, is implemented in the latest laptops in addition to, or as a replacement for, traditional PCMCIA expansion slots.

Whatever the requirement of the mobile contact smart card-based security application, the high-speed ExpressCard™ reader can support it. The OMNIKEY® 4321 uses the USB 2.0 interface as defined by the ExpressCard™ standard for simple integration into laptops or PDA devices. Due to its small size, it is also ideal for mass distribution by mail, bundled in an envelope or small package together with accompanying smart cards and/or software.

- ▶ Compliant with all major standards, including ISO 7816, EMV (Europay®, Mastercard®, Visa®) 2000, Microsoft WHQL, PC/SC, HBCI (Home Banking Computer Interface) and PC-2001 Specification
- ▶ Standard application interfaces include PC/SC, Synchronous-API (on top of PC/SC), OCF (Open Card Framework) or CT-API
- ▶ Robust metal housing with lip for convenient card insertion
- ▶ Supports all major operating systems
- ▶ Meets GSA FIPS 201 requirements
- ▶ Reader can be customized with company logo or corporate colors
- ▶ Reader works with all laptops and PDAs utilizing the ExpressCard™ 54 interface
- ▶ EMV-compliant mobile reader
- ▶ Provides the highest level of interoperability and stability

\* For driver download, please visit [www.omnikey.com](http://www.omnikey.com).

# Specifications

|  |  |
|--|--|
| <b>Base Model Number</b>               | OMNIKEY® 4321  |
| <b>Dimensions</b>                      | 3.00" x 2.13" x 0.20" / 75 x 54 x 5 mm   |
| <b>Weight</b>                          | 0.91 oz / 26 g   |
| <b>Power supply</b>                    | Bus powered  |
| <b>Operating temperature</b>           | 32°-131° F (0° - 55° C)  |
| <b>Operating humidity</b>              | 10-90% rH  |
| <b>HOST INTERFACE</b>                  |  |
| <b>Host Interface</b>                  | ExpressCard™ 54 mm   |
| <b>Transmission speed</b>              | 12 Mbps  |
| <b>SMART CARD INTERFACE</b>            |  |
| <b>Standards</b>                       | ISO 7816 & EMV <sup>2</sup> 2000 Level I   |
| <b>Protocols</b>                       | T=0, T=1, 2-wire: SLE 4432/42 (S=10), 3-wire: SLE 4418/28 (S=9), I <sup>2</sup> C (S=8)  |
| <b>Card size</b>                       | ID-1 (full-size)   |
| <b>Smart Card interface speed</b>      | 420 kbps (when supported by card)  |
| <b>Smart Card clock frequency</b>      | Up to 8 MHz  |
| <b>Supported card types</b>            | 5V, 3V and 1.8V Smart Cards, ISO 7816 Class A, B and C   |
| <b>Power to Smart Card</b>             | 60 mA  |
| <b>Smart Card detection</b>            | Movement detection with auto power-off /Automatic detection of smart card type/ Short circuit and thermal protection   |
| <b>8 Pin Handling</b>                  | C4 / C8 supported  |
| <b>Supported APIs</b>                  | PC/SC driver (ready for 2.01), CT-API (on top of PC/SC), Synchronous-API (on top of PC/SC), OCF (on top of PC/SC)  |
| <b>PC/SC Driver Support</b>            | Windows® 98 / ME, 2000 / XP (32bit), 2003 Server; Windows® CE 5.0 / CE.NET (depending on hardware), Windows® XP 64bit (AMD64, EM64T, IA64), Windows® Vista (32bit / 64bit), Linux® |
| <b>Embedded Technology</b>             | OMNIKEY® Smart@Link Chipset  |
| <b>Color</b>                           | Metallic   |
| <b>Options</b>                         | <b>Customer Specific Logo and Label:</b> Available upon request  |
| <b>Composition</b>                     | Alloy  |
| <b>Durability</b>                      | 30,000 insertions  |
| <b>Meantime between failure (MTBF)</b> | 500,000 hours  |
| <b>Compliance / Certification</b>      | Microsoft® WHQL <sup>3</sup> , EMV <sup>2</sup> 2000 Level I, ISO 7816, HBCI <sup>4</sup> , CCID, GSA FIPS 201 approved product list   |
| <b>Safety / Environmental</b>          | CE, WEEE, UL, FCC, VCCI (in preparation), MIC (in preparation)   |
| <b>Warranty</b>                        | Two year manufacturer's warranty. (For drivers, see complete lifetime support policy.)   |

I = Chip Card Interface Device, 2 = Europay® MasterCard® Visa®, 3 = Windows® Hardware Quality Lab, 4 = Home Banking Computer Interface



© 2008 HID Global Corporation. All rights reserved. HID, the HID logo, Omnikey and the Omnikey logo are trademarks or registered trademarks of HID Global in the U.S. and/or other countries. All other trademarks, service marks, and product or service names are trademarks or registered trademarks of their respective owners. Rev. 08/2008

MKT-OMNIKEY\_4321\_DS-EN



## ACCESS experience.

hidglobal.com

HID Global Offices:

**Corporate North America**  
15370 Barranca Pkwy  
Irvine, CA 92618  
U.S.A.  
Phone: (800) 237-7769  
Phone: +1 (949) 598-1600  
Fax: +1 (949) 598-1690

**Asia Pacific**  
19/F 625 King's Road  
North Point  
Island East  
Hong Kong  
Phone: +852 3160-9800  
Fax: +852 3160-4809

**Latin America**  
Circunvalacion Ote. #201 B  
Despacho 2  
Col. Jardines del Moral  
Leon 37160, Gto.  
Mexico  
Tel: +52 477 779 1492  
Fax: +52 477 779 1493

**Europe, Middle East & Africa**  
Haverhill Business Park  
Phoenix Road  
Haverhill, Suffolk  
CB9 7AE  
England  
Phone: +44 (0) 1440 714 850  
Fax: +44 (0) 1440 714 840