

OMNIKEY® 5125 USB Prox

Contact and Contactless Prox Card Reader

- ▶ **Broad Use** – Reads unique number from HID Proximity cards, the industry standard for access control
- ▶ **Plug-and-Play** – Designed to facilitate easy device installation and automatic configuration
- ▶ **Easy Development** – Compliant with a variety of financial institution standards
- ▶ **Vertical and Horizontal Card Insertions** – Multiple base mounting options suit any application



ACCESS quality.

The OMNIKEY® 5125 is a high-performance, USB smart card reader for desktop use that can be used with any proximity card. Complete with multiple base mounting options and a robust housing, the OMNIKEY® 5125 is compliant with all industry standards. Designed to facilitate ease-of-use, this dual-interface (contact/contactless) reader works with your existing HID Prox cards enabling implementation of new logical access applications without re-badging.

Practical and affordable, the 5125 reader is easy-to install and has a transmission speed to the card of up to 420 kbps, making it an ideal solution for a variety of contact smart card operations, including online-banking and/or digital signature applications.

- ▶ Robust housing and long USB cable for increased convenience and reliability
- ▶ Supports a variety of PC/SC drivers for contact interface
- ▶ Equipped with an interchangeable standing base for both vertical and horizontal configurations and easily mounts to any PC monitor
- ▶ Supports ISO 7816 and EMV (Europay®, MasterCard®, Visa®), Microsoft WHQL, and HBCI (Home Banking Computer Interface) industry standards for contact cards
- ▶ Meets EMV (Europay, MasterCard, Visa), Microsoft WHQL, and HBCI (Home Banking Computer Interface) industry standards for contact cards
- ▶ RoHS / WEEE- complaint
- ▶ Broad Use – Reads unique number from HID Proximity cards, the industry standard for access control (26-bit format up to Corporate 1000 format supported)

Specifications

Base Model Number	OMNIKEY® 5125
Dimensions	3.15" x 2.64" x .11" (80 x 67 x 28 mm)
Weight (Reader only) / Reader with heavy standing base)	Approx. 3.88 oz (110 g) Approx. 7.4 oz (210 g)
Power supply	Bus powered
Operating temperature	32°-131° F (0° - 55° C)
Operating humidity	10-90% rH
HOST INTERFACE	
Host Interface	USB 2.0 CCID ¹ (also compliant with USB 1.1)
Transmission speed	12 Mbps (USB 2.0 full speed)
SMART CARD INTERFACE	
Standards	ISO 7816 & EMV ² 2000 Level 1
Protocols	T=0, T=1, 2-wire: SLE 4432/42 (S=10), 3-wire: SLE 4418/28 (S=9), I ² C (S=8)
Card size	ID-1 (full-size)
Smart Card interface speed	420 kbps (when supported by card)
Smart Card clock frequency	Up to 8 MHz
Supported card types	5V, 3V and 1.8V Smart Cards, ISO 7816 Class A, AB and C
Power to Smart Card	60 mA
Smart Card detection	Movement detection with auto power-off /Automatic detection of smart card type/ Short circuit and thermal protection
8 Pin Handling	C4 / C8 supported
Contactless smart card interface frequency	HID Prox 125 kHz
Supported APIs	PC/SC driver, CT-API (on top of PC/SC, for contact interface), OCF (on top of PC/SC, for contact interface), Synchronous API (on top of PC/SC, for contact interface)
PC/SC Driver Support	Windows® 98 / ME, 2000 / XP (32bit), 2003 Server, Windows® CE 5.0 / CE.NET (depending on hardware), Windows® XP 64bit (AMD64, EM64T, IA64), Windows® Vista (32bit / 64bit), Linux®, Mac® OS X
Status indicator	Two LED (green=ready, red=busy)
Color	Dark Grey
Options	Customer specific logo, label or color: Available upon request Jumbo Standing Base: Available upon request
Mounting (standard base)	Includes adhesive attachment pad and vertical mounting option
Reader Board	Available as PCB
Composition	ABS
Connector cable	70.9" (180 cm)
Durability	100,000 insertions
Meantime between failure (MTBF)	500,000 hours
Compliance / Certification	Microsoft® WHQL ³ , EMV ² 2000 Level 1, ISO 7816, HBCI ⁴ , USB 2.0 (USB 1.1 compatible), CCID ¹ (contact interface only), GSA FIPS 201 approved product list
Safety / Environmental	CE, FCC, UL, RoHS, WEEE
Warranty	Two year manufacturer's warranty. (For drivers, see complete lifetime support policy.)

1 = Chip Card Interface Device 2 = Europay® MasterCard® Visa® 3 = Windows® Hardware Quality Lab 4 = Home Banking Computer Interface



© 2008 HID Global Corporation. All rights reserved. HID, the HID logo, Omnikey and the Omnikey logo are trademarks or registered trademarks of HID Global in the U.S. and/or other countries. All other trademarks, service marks, and product or service names are trademarks or registered trademarks of their respective owners. Rev. 08/2008 MKT-OMNIKEY_5125_DS-EN

ACCESS experience.

hidglobal.com

HID Global Offices:

Corporate North America
15370 Barranca Pkwy
Irvine, CA 92618
U.S.A.
Phone: (800) 237-7769
Phone: +1 (949) 598-1600
Fax: +1 (949) 598-1690

Asia Pacific
19/F 625 King's Road
North Point
Island East
Hong Kong
Phone: +852 3160-9800
Fax: +852 3160-4809

Latin America
Circunvalacion Ote. #201 B
Despacho 2
Col. Jardines del Moral
Leon 37160, Gto.
Mexico
Tel: +52 477 779 1492
Fax: +52 477 779 1493

Europe, Middle East & Africa
Haverhill Business Park
Phoenix Road
Haverhill, Suffolk
CB9 7AE
England
Phone: +44 (0) 1440 714 850
Fax: +44 (0) 1440 714 840