

# ProxPro® II Reader

125 kHz Proximity

New Generation Proximity Card Reader • 5455 (Wiegand), 5458 (Clock-and-Data)



## ACCESS reliability.

### Application

HID's ProxPro® II proximity reader for access control combines performance, reliability, and ease of installation into a two-piece, weatherproof potted enclosure. International users will appreciate the multilingual installation manual, lower voltage requirement and flexible mounting options.

### Features


- ▶ Two-piece reader design allows for easy installation.
- ▶ Available with a Wiegand or Clock-and-Data interface.
- ▶ Provides high reliability, consistent read range and low power consumption.
- ▶ Features include multicolor LED and internal or host control of the LED and beeper.
- ▶ Mounts directly on metal with minimal impact on the read range performance. Optional kit enables mounting behind glass.

Feature	ProxPro	ProxPro II
Multilingual installation manual	No	Yes
Glass mounting kit (optional)	Yes	Yes
Supply Voltages	12V and 24V	5V and 12V
Voltage Range min/max	10 / 28.5VDC	5 / 16VDC
Current Draw avg/peak	100 / 120 mA	25 / 125 mA
Read Range at 12VDC (Proxcard® II/ISOProx® II)	8" (20 cm) / 7" (17 cm)	9" (22 cm) / 8" (20cm)
IP Rating	IP55	IP65
European/Asian mounting holes	No	Yes (vertical)
Weatherproofing method	Rubber O ring	Fully potted electronics
Cover installation method	4 screws, then snap in bezel	Snap on cover
Custom molded logo	No	Available (one-time tooling charge)
Termination method	Screw Terminals	Wire Pigtail
Metal compensation	Jumper	No, but provides equivalent performance on metal
LED/Beeper configuration	DIP Switch or Command Card	Command Card
Custom Firmware	Socketed Processor, change part	Order from factory
Tamper Switch	Yes	No, but electronics are potted to prevent tampering
Keypad Version available	Yes	No
Wiegand Pullup Select 5 or 12V	DIP Switch	No
Serial Version available	Yes	No

Compare features of the ProxPro II to the original ProxPro reader (still available):

## Features

<b>Installation</b>	Easy, streamlined installation procedure is consistent with HID's ThinLine® II, MiniProx® and ProxPoint® Plus readers. Included installation manual features instructions in English, French, German, Spanish, Portuguese, Chinese and Japanese.
<b>Mounting</b>	Mounts on a single-gang electrical box for easy installation. Mounting holes are provided for European and Asian J-boxes. Mounts directly on metal with minimal impact on read range performance. An optional kit enables mounting behind glass.
<b>Audiovisual Indication</b>	An LED flashes green and the beeper sounds when a proximity card is presented to the reader. The multicolor LED and beeper can also be controlled individually by the host system.
<b>Diagnostics</b>	On reader power-up, an internal self-test routine checks and verifies the setup configuration, determines the internal or external control of the LED and beeper and initializes reader operation. An additional external loop-back test allows for the reader outputs and inputs to be verified without the use of additional test equipment.
<b>Indoor/outdoor Design</b>	Sealed in a rugged, weatherized polycarbonate enclosure designed to withstand harsh environments, providing reliable performance and a high degree of vandal resistance. Two-piece reader design allows for easy installation.
<b>Easily Interfaced</b>	Wiegand output model interfaces with all existing Wiegand protocol access control systems. Clock-and-Data (magnetic stripe) model interfaces with most systems that accept magnetic stripe readers.
<b>Security</b>	Recognizes card formats up to 84 bits, with over 1.93x10 <sup>25</sup> unique codes.
<b>Warranty</b>	Lifetime warranty against defects in materials and workmanship (see complete sales policy for details).
<b>Options</b>	<ul style="list-style-type: none"><li>Termination: 18" (45 cm) pigtail standard, 9' (2.7m) available by special order.</li><li>Mounting: glass mounting kit available separately</li><li>Color: white, beige, charcoal gray or black</li><li>LED and beeper operation</li></ul>
<b>Part Numbers</b>	Base Part Number: 5455 Wiegand Base Part Number: 5458 Clock-and-Data interface
<b>Description</b>	Tri-State LED, internal beeper on Glass Mount Kit: 5455AGM00  Please see "How to Order Guide" for a description of the options and associated part numbers. The How to Order Guide can be downloaded in PDF format from: <a href="http://www.hidcorp.com/support">www.hidcorp.com/support</a> .



## Specifications

### Typical Maximum\* Read Range

ProxCard® II card - up to 9" (22 cm)  
ISOProx® II card - up to 8" (20 cm)  
DuoProx® II card - up to 8" (20 cm)  
Smart ISOProx® card - up to 8" (20 cm)  
Smart DuoProx® card - up to 8" (20 cm)  
HID Proximity and MIFARE® card - up to 8" (20 cm)  
ProxCard® Plus card - up to 4" (10 cm)  
ProxKey® II keyfob - up to 4" (10 cm)  
MicroProx® Tag - up to 4" (11 cm)

\*Depending on local installation conditions.

### Dimensions:

5.00" x 5.00" x 1.00"  
(12.7 x 12.7 x 2.54 cm)

**Material:** Polycarbonate UL 94

### Power supply:

5-16 VDC

Linear power supplies are recommended.

### Current requirements:

Average: 25 mA at 12VDC

Peak: 125 mA at 12VDC

### Operating temperature:

-22° to 150° F (-30° to 65° C)

### Operating humidity:

0-95% relative humidity non-condensing

**Weight:** 13.6 oz. (385 g)

**Transmit frequency:** 125 kHz

**Excite frequency:** 125 kHz

### Certifications:

Canada/UL 294 Listed, FCC Certification, United States, Canada Certification, CE Mark, EU and CB Scheme Electrical Safety (EN60950 and IEC60950 ITE Electrical Safety) Fifteen EU Countries under the R&TTE Directive (EN 300 330 - SRD, and ETS 300 683 - EMC), Australia C-Tick (pending), New Zealand (pending), Taiwan (pending)


### Cable distance:

Wiegand interface: 500 feet (150 m)

Clock-and-Data interface: 50 feet (15 m)

Recommended cable is ALPHA 1295 (22 AWG) 5 conductor minimum stranded with overall shield or equivalent. Additional conductors may be required for LED or beeper control.

© 2007 HID Global. All rights reserved. HID, and the HID logo are trademarks or registered trademarks of HID Global in the U.S. and/or other countries. All other trademarks, service marks, and product or service names are trademarks or registered trademarks of their respective owners. Rev. 4/2007



MKT-PROXPROII\_DS\_EN



**ACCESS** experience.

[hidcorp.com](http://hidcorp.com)

#### HID Global Offices:

**Corporate North America**  
9292 Jeronimo Road  
Irvine, CA 92618-1905  
U.S.A.  
Phone: (800) 237-7769  
Phone: (949) 598-1600  
Fax: (949) 598-1690

**Asia Pacific**  
19/F 625 King's Road  
North Point  
Island East  
Hong Kong  
Phone: +852 3160-9800  
Fax: +852 3160-4809

**Latin America**  
Circunvalacion Ote. #201 B  
Despacho 2  
Col. Jardines del Moral  
Leon 37160, Gto.  
Mexico  
Phone: +52 477 779 1492  
Fax: +52 477 779 1493

**Europe, Middle East & Africa**  
Homefield Road  
Haverhill, Suffolk  
CB9 8QP  
England  
Phone: +44 (0) 1440 714 850  
Fax: +44 (0) 1440 714 840