

pivCLASS[®]
Biometric Reader

Meets NIST assurance-level requirements for these areas:

- “Unrestricted” Areas
- “Controlled” Areas
- “Limited” Areas
- “Exclusion” Areas



BIOMETRIC READER FOR “EXCLUSION” AREAS FOR HIGH SECURITY, INTEROPERABILITY AND COMPLIANCE

- **Part of an integrated solution from a single, trusted provider** – Enables compliance per NIST SP 800-116 guidelines and the TWIC Reader Specification.
- **Contact biometric (BIO) reader solution for “Exclusion” security areas** – Meets NIST’s “Exclusion” assurance-level requirements with three-factor PIV + PIN + BIO authentication.
- **Supports multiple card types** – Works with PIV, PIV-I, CAC, CIV (a.k.a., PIV-C), TWIC, FRAC and iCLASS[®] cards for easy, phased transitions from legacy technology to new PKI-enabled smart cards.

ADDITIONAL PRODUCT FEATURES:

- Architected for maximum security and affordability, the reader utilizes the pivCLASS Authentication Module to provide cryptographic functionality and to pass Wiegand-formatted data to the PACS controller. Locating the critical security operations within the secure perimeter (rather than on the attack side of the door) increases security and reader affordability.
- Up to two pivCLASS readers can connect to a pivCLASS Authentication Module via four-wire RS-485 communication to the reader, typically enabling facilities to reuse much of their existing wiring.
- Mountable on single- and double-gang boxes with a width of roughly a double-gang device.
- Available with either a pigtail or terminal strip wiring termination.
- Supports CHUID, CAK, PKI + PIN and PIV + PIN + BIO authentication modes, which can be dynamically changed from a central location.

HID Global’s pivCLASS[®] Government Solutions portfolio makes it possible for facilities to upgrade their existing physical access control system (PACS) to achieve FIPS 201 compliance.

The pivCLASS Biometric Reader (RKCLB40) delivers the “Exclusion” assurance level defined in the National Institute of Standards and Technology (NIST) SP 800-116 guidelines. This reader works with the pivCLASS Authentication Module (PAM) to perform three authentication checks: **PIV + PIN + BIO**.

PIV: The pivCLASS system first determines the validity of the PIV card and its certificates using public key cryptography-based authentication. For instance, the system verifies the digital signature and performs path validation on the PIV authentication certificate and the biometric template data object.

PIN: As part of the PIV verification process, the cardholder must enter a PIN to unlock the card in order to retrieve the PIV certificate and biometric template.

BIO: After the card and its contents have been validated, the pivCLASS system compares the reference biometric template stored on the card with the biometric sample from the live finger.

If successful, three factors of authentication have been achieved. Only then will the pivCLASS system pass the appropriate cardholder ID data to the PACS controller for an access decision.

This three-factor authentication protects against cards that have been revoked, counterfeited, altered, copied, cloned, lost, stolen or shared.

Optionally, the reader’s authentication mode can be lowered by the PAM to accommodate areas with reduced security requirements. This authentication mode can be dynamically changed from a central location in response to threat level, time of day or day of week.

The pivCLASS Biometric Reader is guaranteed to meet the stringent specifications for operation, reliability and interoperability with other Genuine HID[®] products.

SPECIFICATIONS



Model Name	RKCLB40
Base Part Number	924NPR
Specifications	Final
13.56 MHz Card Compatibility	PKI-Based FIPS-201 Credentials including PIV, PIV-I, CIV, CAC, TWIC and FRAC
System Requirements	These readers require HID Global's pivCLASS Authentication Module (M2000) to support FICAM compliance
Typical Contactless Read Range¹	FIPS 201 type cards can be read using either the contact or contactless card interface Biometric authentication only available on the contact interface per FIPS 201
	FIPS 201 Type Cards, Contactless Interface PIV, PIV-I, CIV, CAC, TWIC and FRAC
	1" (2.5 cm)
	13.56 MHz iCLASS, DESFire and MIFARE Cards
iCLASS SE*	4.5" (11 cm)
DESFire* EV1 and HID SE™	2" (5 cm)
MIFARE* Classic and HID SE™	4" (10 cm)
Mounting	Double-gang size; designed to mount on double (preferable for stable wall mount) or single-gang switch box
Color	Black
Keypad	Yes (illuminated, 4 x 3)
Dimensions	4.8" x 6.1" x 1.2" (12.2 cm x 15.6 cm x 3.0 cm)
Product Weight (Pigtail)	17.0 oz (484 g)
Product Weight (Terminal Strip)	16.0 oz (454 g)
Operating Voltage Range	+12VDC
Current Draw - Normal Standby Current²	165 mA
Current Draw - Maximum Average³	215 mA
Current Draw - Peak⁴	275 mA
Operating Temperature	14° to 122° F (-10° to 50° C)
Operating Humidity	5% to 95% relative humidity non-condensing
Storage Temperature	-67° to 185° F (-55° to 85° C)
Environmental Rating	UL 294 and IP55 outdoor ratings
Fingerprint Biometric Sensor Type	Optical
Transmit Frequency	13.56 MHz
Protocol	HID Global pivCLASS Protocol, CoreStreet Reader Protocol
Cable Distance	Six conductor connections per reader: full duplex four-wire RS485 for communication (500 ft [152m], 22AWG), (300 ft [91m], 24AWG); two wires for power (500 ft [152m], 22AWG)
Wiring Connection	Pigtail or Terminal Strip
Certifications	FICAM tested, UL294 (U.S. & Canada), FCC Certification (U.S.), RoHS2
Housing Material	UL94 Polycarbonate
UL Ref Number	RKCLB40E
Warranty	Warranted against defects in materials and workmanship (see complete warranty policy for details)

¹ Typical read range in air. Different types of metal will cause some degradation (typically up to 20%). Use spacers to space product off metal and improve read range if required.
Read ranges for FIPS 201 type cards will vary depending on the card manufacturer.
² Standby Average - RMS current draw without a card in the RF field.
³ Maximum Average - RMS current draw during continuous PIV card reads.
⁴ Peak - highest instantaneous current draw during RF communication.
⁵ FICAM-tested as part of complete physical access control system.



hidglobal.com

North America: +1 512 776 9000
Toll Free: 1 800 237 7769
Europe, Middle East, Africa: +49 6123 791 0
Asia Pacific: +852 3160 9800
Latin America: +52 55 5081 1650

© 2015 HID Global Corporation. All rights reserved. HID, HID Global, the HID Blue Brick logo, the Chain Design, pivCLASS, iCLASS SE, MIFARE, DESfire, Seos, Prox, and Genuine HID are trademarks or registered trademarks of HID Global in the U.S. and/or other countries. All other trademarks, service marks, and product or service names are trademarks or registered trademarks of their respective owners.
2015-10-29-hid-pivclass-fips-readers-exclusion-ds-en PLT-00414

An ASSA ABLOY Group brand

ASSA ABLOY