



## **Key Features**

DS-1002HMI-S backup device is designed to back-up the recorded video data from DS-8000HMI/HMFI mobile DVR. High-speed back-up, settings and other auxiliary operations are also available. It is an optional device for Hikvision DS-8000HMI/HMFI series mobile DVR.

The backup device DS-1002HMI-S can be connected to mobile DVR with e-SATA interface and backup recorded video data in any specified time frame. Mobile DVR video output also can be connected to DS-1002HMI-S video input in order to use DS-1002HMI-S LCD to display mobile DVR menu.

After the back-up, DS-1002HMI-S can be connected to PC via USB, SATA or 1394 interface to playback the video data.

## **Specifications**

## Interface

SATA Interface 1

External Interface 1 e-SATA Interface

2 1394 Interfaces

1 USB2.0 Interface

Video Input 1 Ch, BNC (1.0Vp-p, 750hm)

## General

Power Supply 12VDC

Power Supply Adapter 100

100V ~ 240V Input and 12VDC

Output

Power consumption 10W (w/o HDD) Operating Temperature  $-20^{\circ}\text{C} \sim 65^{\circ}\text{C}$ 

Humidity 10%~90% Size 195mm(W)x170mm(H)

x80mm(D)

Weight 2Kg (w/o HDD)

LCD 5.5" Color TFT LCD Monitor

www.hikvision.com 41