

DS-4216HCI Compression Card



Key Features

- Adopts high-efficiency video processing chips
- Extra-low power consumption and high stability
- Standard H.264 video codec
- CIF real-time audio/video capturing and encoding
- Support multiple cards plugged in PC (support up to 40ch cameras input for 1 PC)
- Built-in motion detect
- Support OSD, LOGO and mask area settings

Specifications

		DS-4216HCI
Video/Audio input	Video compression	H.264(MPEG-4/part10)
	Video input	16-ch
	Video input interface	BNC (1.0Vp-p, 75Ω)
	Audio compression	OggVorbis
	Audio input	16ch, mono
	Audio input interface	BNC (2Vp-p, 1kΩ, volume adjust range: 83DB)
Video/Audio output	Preview resolution	4CIF real time
	Compression resolution	CIF/QCIF real time; 4CIF/2CIF not real time
	Video bit rate	32k~2M (CIF), 32k~4M (4CIF) (Unit:bps)
	Sampling Rate	8KHz
	Audio Recording Bit Rate	64kbps
	Dual Stream	Yes
	PCI Standard	PCI 2.2
General	Power consumption	< 8.5W
	Working temperature	-10°C~+50°C(14°F~122°F)
	Working humidity	10%~90%
	Dimension	162x101mm(6.38"x3.98")