

## DS-4208/4216HFVI Compression Card



DS-4208HFVI



DS-4216HFVI

### Key Features

- Adopts high-efficiency video processing chips
- Extra-low power consumption and high stability
- Standard H.264 video codec
- 4CIF real-time audio/video capturing and encoding
- Support multiple cards plugged in PC (support up to 40ch cameras input for 1 PC)
- Built-in motion detect
- Support OSD, LOGO and mask area settings

### Specifications

		DS-4208HFVI	DS-4216HFVI
Video/Audio input	Video compression	H.264(MPEG-4/part10)	
	Video input	8-ch	16-ch
	Video input interface	BNC (1.0Vp-p, 75Ω)	
	Audio compression	OggVorbis	
	Audio input	8ch, mono	16ch, mono
	Audio input interface	BNC (2Vp-p, 1kΩ, volume adjust range: 83DB)	
Video/Audio output	Preview resolution	4CIF real time	
	Compression resolution	4CIF/2CIF/CIF /QCIF real time	
	Video output	1 channel BNC video output	
	Video bit rate	32k~2M (CIF), 32k~4M (4CIF) (Unit:bps)	
	Sampling Rate	8KHz	
	Audio Recording Bit Rate	64kbps	
	Dual Stream	Yes	
General	PCI Standard	PCI 2.2	
	Power consumption	< 7W	< 14W
	Working temperature	-10°C~+50°C(14°F~122°F)	
	Working humidity	10%~90%	
	Dimension	162x101mm(6.38"x3.98")	213x101mm(8.39"x3.98")