

DS-7008HI-S Standalone DVR



Key Features

- Each channel supports up to 2CIF encoding
- Video loop output interface
- VGA output
- 4 SATA interface
- Support main and auxiliary video output

Specifications

Video/Audio Input

Video Compression	H.264
Video Input	8
Video Input Interface	BNC (1.0Vp-p, 75Ω)

Hard Disk Drive

Interface	SATA x 4
Capacity	Each HDD Supports Up to 2000GB

Video/Audio Output

Display	PAL: 704x576 NTSC: 704*480
Recording Resolution	2CIF/CIF/QCIF
Main Video Output	1 Ch, BNC (1.0Vp-p, 75Ω)
Aux Video Output	1 channel, BNC (1.0Vp-p, 75Ω)
Video Loop Output	8
Recording/Playback	2CIF: 8fps CIF: 25(P)/30(N) fps 32Kbps ~ 8Mbps
Bit Rate	32Kbps ~ 8Mbps
VGA Output	1, Support 800x600 (60Hz), 1024x768 (60Hz), 1280x1024 (60Hz)

External Interface

Communication Interface	1 RJ45 10M/100M Ethernet Port
	1 RS232 Port
RS-485 Port	1 (T+, T-, R+, R-)
USB Interface	1
Alarm Input	16 (Terminal Block)
Alarm Output	4 (Terminal Block)

General

Power Supply	100~240VAC, 6.3A, 50~60HZ
Power Consumption	≤70W (w/o HDD or DVD-R/W)
Operating Temperature	-10°C ~ 55°C
Humidity	10% ~ 90%
Chassis	19" Standard
Dimensions	440mm(W)x390mm(D) 70mm(H)
Weight	≤8Kg (w/o HDD or DVD-R/W)