


DS-7600NI-SE/N Series NVR



Features and Functions



- Connectable to the third-party network cameras like AXIS, ONVIF, PANASONIC, PSIA, SAMSUNG and SANYO.
- Up to 16 network cameras can be connected.
- Support live view, storage, and playback of the connected camera with up to the resolution of 5 megapixels.
- Simultaneous HDMI and VGA outputs at up to 1920×1080 resolution.
- New GUI and support starting record with one key;
- Redundant recording and holiday recording;
- Realize instant playback for assigned channel during multi-channel display mode.
- Up to 8-ch synchronous playback at 4CIF resolution.
- Customization of tags, searching, and playing back by tags.
- Locking and unlocking record files.
- Support HDD quota and group modes; different capacity can be assigned to different channel.
- Up to 2 SATA hard disks can be connected, for both recording and backup.
- 1 self-adaptive 10M/100M/1000M network interface;
- Up to 8 independent network interfaces with built-in switch function are provided;
- Support Hikvision DDNS (Dynamic Domain Name System);
- Support network detection, including network delay, packet loss, etc.



Specifications

Model		DS-7604NI-SE/N	DS-7608NI-SE/N	DS-7616NI-SE/N
Video/Audio input	IP video input	4-ch	8-ch	16-ch
	Two-way audio input	1-ch, RCA (2.0 Vp-p, 1kΩ)		
Network	Incoming bandwidth	20Mbps	40Mbps	80Mbps
	Output bandwidth	40Mbps		
	Remote connection	128		
Video/Audio output	Recording resolution	5MP/3MP/1080p/UXGA/720p/VGA/4CIF/DCIF/2CIF/CIF/QCIF		
	HDMI/VGA output	1-ch, resolution: 1920 × 1080P /60Hz, 1600 × 1200 /60Hz, 1280 × 1024 /60Hz, 1280 × 720 /60Hz, 1024 × 768 /60Hz		
	Audio output	1-ch, RCA (Linear, 1kΩ)		
	Playback resolution	5MP /3MP /1080P /UXGA /720P /VGA /4CIF /DCIF /2CIF /CIF /QCIF		
	Synchronous playback	4-ch, 720P / 2-ch, 1080P / 1-ch, 5MP	8-ch 4CIF /4-ch, 720P / 2-ch, 1080P / 1-ch, 5MP	
Hard disk	SATA	1 SATA interface for 1 HDD	2 SATA interfaces for 2 HDDs	
	Capacity	Up to 4TB for each disk		
External interface	Network interface	1 RJ-45 10 /100 /1000 Mbps self-adaptive Ethernet interface		
		4 independent 10 /100 Mbps built-in switch Ethernet interfaces	8 independent 10 /100 Mbps built-in switch Ethernet interfaces	
	Serial interface	1 RS-485 half-duplex interface		
	USB interface	2 × USB 2.0		
	Alarm in/out (optional)	4/1		
Others	Power supply	12 VDC		
	Consumption	≤ 10 W (without hard disk)		
	Working temperature	-10 °C ~ +55 °C		
	Working humidity	10 % ~ 90 %		
	Chassis	Stand-alone 1U chassis	19-inch rack-mounted 1U chassis	
	Dimensions (W × D × H)	315 × 230 × 45mm	445 × 290 × 45mm	
Weight	≤ 2 Kg (without hard disk)			

Physical Interfaces



Index	Description	Index	Description
1	LAN Network Interface	7	HDMI Interface
2	RS-485 Interface	8	VGA Output
3	Power Supply	9	Audio In
4	Power Switch	10	Audio Out
5	USB Interface	11	Network Interfaces with built-in switch function
6	GND		

Available Models

DS-7604NI-SE/N, DS-7608NI-SE/N and DS-7616NI-SE/N.

Distributed by



Headquarters

No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
overseasbusiness@hikvision.com

Hikvision Poland
T +48-22-460-01-50
poland@hikvision.com

Hikvision USA
T +1-909-895-0400
sales.usa@hikvision.com

Hikvision India
T +91-22-28469900
sales@pramahikvision.com

Hikvision UK
T +44-1628-9021-4
support.uk@hikvision.com

Hikvision Europe
T +31-23-5542770
saleseuro@hikvision.com

Hikvision Italy
T +39-0438-6902
info.it@hikvision.com

Hikvision Singapore
T +65-6684-4718
sg@hikvision.com

Hikvision Middle East
T +971-4-8816086
salesme@hikvision.com

Hikvision France
T +33(0)1-85-330-444
info.fr@hikvision.com

Hikvision Oceania
T +61-2-8599-4233
salesau@hikvision.com

Hikvision Russia
T +7-495-669-67-99
saleru@hikvision.com

Hikvision Spain
T +34-91-737-16-55
info.es@hikvision.com

Hikvision Hong Kong
T +852-2151-1761