


DS-8104/08/16HWI-ST 960H Standalone DVR



Key features

- H.264 video compression
- WD1(PAL:960×576,NTSC:960×480) resolution real-time recording
- HDMI and VGA output at up to 1920×1080P resolution
- Dual-stream
- 4/8/16-ch synchronous playback
- HDD quota and group management

Rear Panel of DS-8116HWI-ST



1. Video in
2. Audio in
3. Video spot out
4. Video out
5. Audio out
6. Line in
7. RS-232 serial interface
8. VGA interface
9. HDMI interface
10. eSATA interface
11. LAN interface
12. Termination switch
13. RS-485 serial interface, keyboard interface, alarm in, alarm out
14. GND
15. 100 ~ 240 VAC power input
16. Power switch

	DS-8104HWI-ST	DS-8108HWI-ST	DS-8116HWI-ST
Video/Audio input			
Video compression	H.264		
Analog video input	4-ch, BNC(1.0Vp-p, 75 Ω), PAL / NTSC self-adaptive	8-ch	16-ch
Audio compression	OggVorbis		
Audio input	4-ch, BNC (2.0 Vp-p, 1 kΩ)	8-ch, BNC (2.0 Vp-p, 1 kΩ)	16-ch, BNC (2.0 Vp-p, 1 kΩ)
Two-way audio input	1-ch, BNC (2.0 Vp-p, 1 kΩ)		
Video/Audio output			
HDMI / VGA output	1024×768 /60 Hz, 1280×720 /60 Hz,1280×1024 /60 Hz, 1600×1200 /60 Hz, 1920×1080P /60 Hz		
CVBS output	2-ch, (1 Main output+ Spot output), BNC (1.0Vp-p, 75Ω), resolution: PAL: 704×576, NTSC: 704×480		
Video loop out	Reserved		
Audio output	2-ch, BNC		
Encoding resolution	Main stream: WD1 / 4CIF / 2CIF / CIF / QCIF, Sub-stream: CIF / QCIF		
Frame rate	25fps (P) / 30fps /N		
Video bit rate	32 Kbps-8 Mbps, or user defined		
Audio bit rate	16 Kbps		
Dual-stream	Support		
Stream type	Video, Video & Audio		
Playback resolution	WD1 / 4CIF / 2CIF / CIF / QCIF		
Synchronous playback	4-ch	8-ch	16-ch
Hard disk			
SATA	8 SATA interfaces for 4 HDDs + 1 DVD-R/W (default), or 8HDDs;		
eSATA	1 eSATA interface		
Capacity	Up to 4TB capacity for each disk		
External interface			
Network interface	2, RJ45 10M / 100M / 1000M adaptive Ethernet		
Serial interface	RS-232 interface; RS-485 interface;keyboard;		
USB interface	3 x USB2.0		
Alarm in/out	4/2	16/4	16/4
General			
Power supply	100 ~ 240 VAC, 6.3 A, 50 ~ 60 Hz		
Consumption	≤ 35W	≤ 40W	≤ 45W
Working temperature	-10°C ~ +55°C (14°F ~ 131°F)		
Working humidity	10% ~ 90%		
Chassis	19-inch rack-mounted 2U chassis		
Dimensions (W × D × H)	445 × 470 × 90 mm		
Weight	≤ 8Kg (without hard disk or DVD-R/W)		