IS-280CM



The IS-280CM is a commercial ceiling mounted passive infrared motion provides a 360° detection pattern in a sleek, low-profile design housing. performance is achieved by using an advanced microprocessor and 100% tested pyroelectric element.

FEATURES:

- Reliable Performance By combining an advanced microprocessor and 100% tested pyroelectric element, the IS-280CM provides the installed outstanding detection and robust false alarm immunity.
- Fast and Simple Installation Three highly visible walk test LEDs provide easy identification of range from any distance or angle within the detection pattern. Markings on the terminal strip make wiring a snap.
- False Alarm Prevention Features Provides protection against false alarms due to RF signals, electrostatic discharge, and electrical overstress. The bug guard protects the pyroelectric element against insects and unwanted drafts.
- Sleek, Low-Profile Design The slim white housing blends well with any decor. The IS-280CM also has wiring knockouts for either surface or recessed wire runs and can be mounted on a single-gang electrical box.
- Effective in Hot or Cold Environments The IS-280CM operates effectively in harsh environments (14° to 122°F / -10 to 5°C)
- Alarm Memory and First to Latch Provides alarm history when needed

Ceiling Mount Motion Sensor



IS-280CM



SPECIFICATIONS:

Pattern Coverage: 360 Degrees

Range: 46 ft

PIR Fields of View: 50

Alarm Relay:

Form A, SPST, 30VDC 500mA

Power Requirements:

9 to 30VDC I7mA

Operating Temperatures:

14 to 122F (-10 to +50) 95% Humidity (Non-condensing)


Dimensions: 4.9" DIA X 1.5" H


(125mm DIA X 38mm H)

Sensitivity: Selectable 1,2,3,4 Pulses

Tamper: NC 50mA, 24VDC

Ceiling Mount Motion Sensor





165 Eileen Way, Syosset, NY 11791 Copyright ©2003 Honeywell International Inc. ADEMCO is an ISO9001 Registered Company

