

KEYFOBS

DETECTORS



- 5814**
5800 Series mini window contact
- Built in reed switch
 - Dimensions: 42x45x22mm
 - EN50131-1 Security Grade 2, Environmental Class II
 - AVAILABLE REFERENCES:
5814H (2021-021) - 868MHz



- 5808**
5800 Serie wireless combined smoke & heat detector
- Trips when temperatures reach 57° or when smoke is sensed
- Tamper protection
- Photoelectric sensor, clip-off backplate
 - Dimensions: 140mm diameter
 - EN50131-1 Security Grade 2, Environmental Class II.
 - AVAILABLE REFERENCES:
5808H (2021-032) - 868MHz



- 5816**
5800 Series wireless universal contact
- Two loop transmitter, wired external detector, built in reed switch, back plate and off wall tamper
- Dimensions: 78x40x30mm
 - EN50131-1 Security Grade 2, Environmental Class II.
 - AVAILABLE REFERENCES:
5816H (2021-033) - 868MHz
5816HUK (2021-035) - 868MHz
 - ALSO AVAILABLE:
5816BR - 3-pack brown cases
5899 : Four pack magnets



- 5888**
5800 Series wireless PIR detector
- 12m range, look down lens, selectable pet avoidance as standard, selectable pulse count, adjustable view angle
- Size : 70x130x52mm
 - EN50131-1 Security Grade 2, Environmental Class II.
 - **5888H** (2021-034) - 868MHz



- 5819**
5800 Series wireless shock sensor with built in reed switch
- Typical 1.5m radius coverage, fully adjustable sensitivity and pulse count, vertical or horizontal mounting
 - Dimensions: 122x38x25mm
 - EN50131-1 Security Grade 2, Environmental Class II.
 - AVAILABLE REFERENCES:
5819HS (2021-037) - 868MHz



- 5852**
Glass Break Detector
- lithium battery
 - Dimensions: 70x125x27mm
 - AVAILABLE REFERENCES:
5852H (2021-023) - 868MHz