

Wireless Peripherals for Galaxy Intruder Control Panels

5802H Panic Alarm

- Sleek design, fully supervised portable panic alarm
- Dual button action
- Use as a pendant or belt clip
- User-replaceable lithium battery
- LED transmission indication



(85x50x20mm)

5804H Keyfob

- Small sleek wireless key offering many of the features of a keypad
- Four programmable buttons
- User replaceable, long life lithium batteries
- One-button set and unset operation
- KEELOQ® rolling code encryption for added security



(65x40x11mm)

5808H Smoke Detector

- Combined smoke sensor and heat detector
- Trips when temperatures reach 57° C or when smoke is sensed
- Wireless installation provides flexibility as well as quick and easy installation
- Photoelectric sensor
- Tamper protected
- Clip off back plate



(140mm dia x 53mm)

5816H Universal Contact

- Door and window protection
- Two loop transmitter
- Built in magnetic reed switch
- Allows wired detector to signal to wireless receiver



(90x40x28mm)

5888H PIR

- 12 metre range passive infrared detector
- Look down lens
- Selectable pet avoidance as standard
- Selectable pulse count
- Adjustable view angle



(130x75x60mm)

5814H Mini Window or Door Contact

- Very small, discreet wireless switch
- Built-in magnetic reed switch



(45x42x21mm)

5852H Glassbreak

- Audio glassbreak detector
- 7.5 metre range
- Adjustable sensitivity
- Test mode with LED display



(120x105x31mm)

5819H Shock Sensor

- Shock sensor with built-in reed switch
- Typical 1.5 metre radius coverage
- Fully adjustable sensitivity and pulse count
- Vertical or horizontal mounting



(130x39x30mm)

Galaxy RF RIO

- Acts as a wireless receiver allowing the wireless peripherals to be supported on the Galaxy panel range (not available on the Galaxy 16*plus* or Galaxy 8)
- Connected directly to the Galaxy panel (via direct cable connection) but can be mounted up to 1000m from the control panel
- Support for up to 32 zones (dependant on panel zone capacity)
- Support for up to 30 wireless keyfobs
- Built-in signal strength meter
- 4 hard-wired programmable outputs

Compatible with Galaxy 18-512 control panels (V4 upwards)



(170x149x40mm)

All products except RF RIO include rechargeable batteries
All wall/ceiling mounted devices are tamper protected

Residential and Commercial Solutions