



WIDE VARIETY OF FEATURES

External Sounder

AG3

External Sounder



Polycarbonate Housing
116 dBA peak @ 1 metre Piezo
Sounder
2 Watt Xenon Strobe Tube
Screw and Back Tamper
6V Rechargeable Battery (NiCd/NiMH)

20 Minute Dual Failsafe Cut-off Timer /
5 Second Engineer Sounder Test
Alternating LED's
Red Led Indicates Tamper Switch
Closed
Green LED Indicates Supply / Hold Off

Voltage Present
Sweep Sounder Sound
Battery On - Off, Selectable by
Moveable Jumper link
2 Year Warranty
CE Marked

SPECIFICATIONS

Dimensions	315mm 185mm 70 (l mm w mm h)
Actuation	Screw & Back
Return Signal	NT Negative switched via tamper switch
Working Voltage	13.2V Nominal (10 > 15V) SAB Auto Activation 7V Nominal (5 > 9V)
SAB Auto Activation	7V Nominal (5 > 9V)
Standby Current	Alternating LED's 42.5mA, Constant LED's 53.5mA
Battery	6.0V, 280-300 mAH NimH - NiCad
Capacity	280-300mAH
Charge Current	Trickle 5.5mA Nominal, From Discharged 13.8mA Max.
Charge Time	Less than 24 hours
Sounder Current	Single Piezo: 125mA (160mA Max.)
Sound Pressure	Single Piezo: 114dBA@1M (116 dBA Peak@1M)
Operating Temperature	-25°C to +55°C
Humidity	5% -95% Relative humidity, non-condensing
Trigger Conditions	Automatic reset occurs when trigger clears
Triggers	Loss of hold off supply, S-Negative Trigger (-V applied), Trigger occurs when terminal voltage is less than 3.5V, Maximum load 1.0 mA
Electronics	17.X P1 / 34.X P2
Tamper Detection	Wall and cover retaining screw
Cut off Timer	15 minutes nom. (sounder only)
Strobe Trigger	-V applied
Strobe	0.6 Joules per flash, Flash rate 2 flashes per second nom. @ 13.65 VDC strobe supply
Colour Options	Cover: White, Red, Yellow Lens: Blue, Red, Clear Amber
Product Coating	HPA, High Performance Acrylic
Standards	EN50131-1:1997 Grade 3 & PD6662:2004 (prEN50131-1: 2004) Grade 3, Environmental Class IV, CE, EEC, EMC
Warranty	2 Years from date of Manufacture, Date of Manufacture Marked on PCB.

Honeywell Security
Honeywell International Inc.
Newhouse Industrial Estate
Motherwell
Lanarkshire ML1 5SB
Scotland
Tel +44 (0)1698 73 8200
www.honeywell.com/security/uk/intruder

HSCE-AG3-01-EN(11/05)SB-B
© 2005 Honeywell International Inc.

Honeywell