



ATTRACTIVELY STYLED WITH UNSURPASSED PERFORMANCE

## **Adjustable Range Glassbreak Detector**

# FG-1615



## Adjustable Range Glassbreak Detector

FlexCore™ Signal Processor  
Easy Installation and Setup  
Mount the Detector Anywhere  
Covers All Glass Types

Multiple Domain Signal Analysis  
Remote Test Mode Enable/Disable  
Enclosed PC Board

## SPECIFICATIONS

<b>Dimensions:</b>	98mm x 62mm x 21.8mm (h x w x d)
<b>Weight:</b>	90g
<b>Range:</b>	4.6m maximum, omnidirectional no minimum range
<b>Alarm Relay:</b>	1615 Form A, 125mA max, 25 VDC max 1615T Form C, 125mA max, 25 VDC max
<b>Tamper Switch:</b>	Combination cover and wall tamper, 25 mA max, 24 VDC max (Fg1615T only)
<b>Alarm Duration:</b>	5 Seconds (unaffected by alarm LED latching)
<b>ESD Immunity:</b>	10 kV discharges of either polarity to exposed surfaces
<b>Power Requirements:</b>	6 ~ 18 VDC, 12 mA typical @ 12 VDC 22 mA max (Latched LED), AC ripple: 4 Volts peak-to-peak at nominal 12VDC
<b>RF Immunity:</b>	30 V/m, 10 MHz - 1000 MHz
<b>Operating Temperature:</b>	-10°C ~ 50°C
<b>Approvals:</b>	FCC and IC verified, CE, UL listed, ULC listed, PD6662 & EN50131-1 Security Grade 2 Environmental Grade II

### Glass Type Thickness

Minimum size for all glass types is 28cm x 28cm, square. Glass must be framed in the wall or mounted in a barrier of 0.9m wide.

Type	Min. Thickness	Max. Thickness
Plate <sup>3a</sup>	2.4mm	10mm
Tempered	3mm	10mm
Laminated <sup>1</sup>	3mm	14mm
Wired	6mm	6mm
Coated <sup>2,3b</sup>	3mm	6.4mm
Sealed	3mm	6mm
Insulating <sup>1,3b</sup>	(Maximum overall 7/16")	

<sup>1</sup> Protected only if both plates of the unit are broken.

<sup>2</sup> Coated glass with security films, including films for solar protection, up to 12mm thick may be used. Film Technologies International, Inc's GLASS-GUARD® GGLL 1200 has been evaluated with this product by Underwriters Laboratories, Inc. at IntelliSense's request.

<sup>3</sup> In compliance with Underwriters Laboratories of Canada's Standard for Intrusion Detection Units (CAN/ULC-S306-M89):

<sup>a</sup> Plate glass 3mm to 10mm can be used

<sup>b</sup> ULC recognises a maximum range for protecting sealed insulated glass and coated glass of 2.3m.

Note: The Fg1615/1615T detects shattering of framed glass by direct impact. It may not consistently detect breakage by blows that only crack the glass, by high velocity projectiles such as bullets, or glass broken without an impact



### FlexGuard® Glassbreak Simulator/Tester

The sound of breaking glass is digitally simulated by the FG-701 and is compatible for testing all IntelliSense glassbreak detectors. Testing glassbreak detectors upon installation is highly recommended.

### Accessories

**FG-701:** Glassbreak Simulator



Honeywell Security & Custom Electronics  
2 Redwood Crescent  
East Kilbride  
G74 5PA  
Scotland  
Tel +44 (0)1355 354000  
www.honeywell.com/security/uk/intruder

HSCE-FG1615-01-EN(11/05)SB-B  
© 2005 Honeywell International Inc.

**Honeywell**