

Control Panels | GALAXY 2 SERIES



The Galaxy 2 Series range of alarm panels are ideal for residential and small commercial installations. The range comprises of two control panels, the Galaxy 2-20 and the Galaxy 2-44+ which provide up to 20 and 44 zones respectively. Like all Galaxy control panels the 2 Series is backwards compatible with existing Galaxy alarm systems, making it easy to install in retro-fit applications. While the Galaxy 2-44+ also offers dual bus technology that provides backwards compatibility with Galant panel installations. The Galaxy 2 Series also has the familiar Galaxy user interface and programming architecture for additional installer ease. The 2 Series is a fully hybrid system with support for hardwired and/or wireless peripherals in one installation. In addition to the existing range of wireless sensors, the Galaxy 2 Series is also compatible with the high performance Honeywell Domonial wireless sensors. SMS text signalling using up to three mobile phone numbers can be used for alarm reporting as well as

providing information about the alarm status on site. PC support packages also provide a remote servicing facility. Other options available only on the 2-44+ are a GSM mobile communications module permitting dual path signalling and 2-way voice communications via a speaker/microphone option. This highly flexible range is fully compliant with the requirements of PD6662/prEN50131-1:2004 Security Grade 2 in addition to DD243:2004.

GALAXY 2 SERIES

Feature	Galaxy 2-20	Galaxy 2-44+
Zones	12 to 20	12 to 44
Outputs	4 to 16 (includes 8 Trigger Lead outputs)	4 to 28 (includes 8 Trigger Lead outputs)
Integrated PSU	1A (0.6A @ g2)	1.45A (1A @ g2)
Data bus	1 x RS485	RS485 and ECP
Keypads(Keyprox)	4 (4)	4 (4)
MAX	-	-
Wireless	Yes (Domonial)	Yes (Domonial and/or 5800 Series)
Codes	24	24
Groups	3+1 Common	3+1 Common
7 Day Timer	-	-
Zone Types	21	21
O/P Types	27	27
Library (Words)	-	-
Event Log	384	384
MAX Log	-	-
Multi-Users	4	4
Autoset	-	-
Pre-Check	-	-
Timed Lockout	Yes	Yes
Links	-	-
Link O/P	-	-
Part Set	Yes	Yes
Silent Part Set	Yes	Yes
RS232	Onboard Serial Port ⁽¹⁾	
Integrated PSTN	Yes (V.22)	Yes (V.22)
Printer Output	Yes	Yes
Remote Servicing	Yes	Yes
Ethernet Module	-	-
GSM Modem	-	Optional
2 Way Voice	-	Optional
SMS Text	3 Numbers	3 Numbers
PD6662:2004	Grade 2	Grade 2

⁽¹⁾ Baud rate application dependent.