

HMM17

17 INCH MONOCHROME MONITOR

Honeywell Video's HMM17 is a high quality 17-inch monochrome monitor that is ideal for video surveillance and security applications. The monitor features a sturdy housing and delivers sharp images with over 900 TV lines of resolution. Its large viewing area is advantageous for applications requiring detailed picture-in-picture or multi-screen formats typically associated with quad processors or multiplexers.

The HMM17 has convenient recessed front panel controls making set up and adjustment quick and easy while restricting movement caused by casual contact. Installers can easily switch between EIA and CCIR video formats to comply with worldwide video standards. An illuminated green LED beside the power button confirms that power is being supplied to the monitor. The monitor features a latching power switch which remains in its set position – either on or off – eliminating the need to turn the monitor back on in the event of a power loss.

The HMM17 has two composite BNC connectors with looping outputs. The BNC connectors are auto terminating, eliminating the need for installers to set termination switches when using for loop-through video.

The HMM17 has audio input and output connectors, allowing users to listen in, as well as view the monitored area. This is especially convenient for secured entry areas. Honeywell Video's HMM17 can be easily rack mounted using an optional rack mount kit (HMM17RK1).

Features:

- >900 TVL
- Convenient recessed front panel controls
- Heavy-duty metal cabinet
- EIA or CCIR selectable
- Video loop-through with automatic termination
- A/B Switch for video selection
- Audio Input/Output
- Latching power switch
- Rack mountable

HMM17



HMM17X



HMM17

SPECIFICATIONS:

Technical	
Picture Tube:	17-inch diagonal (43 cm)
Resolution:	>900 TV lines (at center)
Video Standard:	EIA/CCIR
Deflection:	90° angle
Electrical	
Power Source:	90 to 264 VAC, 60 Hz/50 Hz
AC Input Connector:	IEC 320 type connector for AC input
Power Cable:	NEMA 5-15P, UL
Power Consumption:	40 Watts
Scanning Frequency	
Horizontal	60 Hz: 15.734 KHz; 50 Hz: 15.625 KHz
Vertical	60 Hz: 59.94 Hz; 50 Hz: 50Hz
Linearity:	Horizontal: 10% maximum; Vertical: 10% maximum
Video A/B Inputs:	Two sets of BNC connectors for loop-through operation, auto-terminating; Level: 1 Vp-p (75 Ohms); Impedance: 75 Ohms/Hi-Z
Connectors:	Audio (In and Out): 2 RCA Connectors
Controls	
Front:	V-Size •H-Size •V-Size •V-Hold •H-Hold •Bright •Contrast •Sharpness •Volume •Power •Underscan/Overscan
Back:	•V-linearity •DC Restoration On/Off
Environmental	
Operating Temperature:	32° F to 104° F (0° C to 40° C)
Operating Humidity:	0% to 90% (noncondensing)
Mechanical	
Dimensions (W x H x D):	16-11/32"x 14-13/16"x 14-3/16" (415 mm x 376 mm x 361mm)
Weight:	31.5 lbs. (14.3 Kg)
Shipping Weight:	36 lbs., 5 oz. (16.5 Kg)
Regulatory	
Emissions:	FCC Part 15, Class B, Canada ICES-003
Safety:	UL: UL1950, cUL: CSA C22.2 No. 950 DHHS Rules 21
Ordering	
HMM17	17" Monochrome Monitor, black cabinet
HMM17X	17" Monochrome Monitor, grey cabinet

Note: Honeywell reserves the right, without notification, to make changes in product design or specifications.

Honeywell Security

Honeywell Video Systems
2700 Blankenbaker Pkwy, Suite 150
Louisville, KY 40299
800 796 CCTV
www.honeywell.com

L/HMM17a/D
September 2005
©2005 Honeywell International Inc.