


MAXPRO[®] VMS SERVER

Video Management System Server

✓ Now with 5-year warranty

Powered by the latest Intel[®] Xeon[®] processor family, the HMSP3 MAXPRO VMS Server delivers the right mix of performance, redundancy and value in a dense 1-socket, 1U chassis.



SPECIFICATIONS

OPERATIONAL

Operating System	Server 2016
Processor	Xeon E-2134
Memory	16 GB
OS Hard Drive	Dual (RAID1) 250GB SSDs for OS
Data Drive	Bays 4 hot plug data drives
Network	2 x Gigabit Ethernet ports
Video Card	Matrox G200

REAR PANEL CONNECTIONS

USB	2 x USB3.0
Monitor Output	1 x VGA
Ethernet Port	2 x RJ45
Serial Port	1 x RS232 (+ 8 using optional HMS8PUPG card)

ELECTRICAL

Input Voltage	100~240 VAC 50/60 Hz (4.8 A-2.4 A per power supply)
Power Supply	2 x 350 Watt

MECHANICAL

1U RACK MOUNT

Dimensions (W x H x D)	17.08" x 1.68" x 23.45" / 434 x 43 x 596 mm
Weight	26.89 lb (12.2 kg)

ENVIRONMENTAL

Temperature	10°C (50°F) ~ 35°C (95°F)
Relative Humidity	10%~80% non-condensing

REGULATORY

Safety & Emissions	Energy Star, CEC, CECP, FCC, NOM, CCC, UL
--------------------	---

WARRANTY

Warranty and Advanced Replacements	Refer to https://www.security.honeywell.com/resources/warranties
------------------------------------	--

MAXPRO VMS SERVER



ORDERING

HMSP3	MAXPRO VMS Performance Server, 1U, Redundant Power Supply, Server 2016, Xeon E-2134, 16GB
HMS8PUPG	8 serial output card for HMSP3
HMSP3RAM32G	16 to 32 GB memory Upgrade Kit for HMSP3 MAXPRO VMS Server

For more information

www.security.honeywell.com

Honeywell Commercial Security

715 Peachtree St. NE

Atlanta, GA 30308

1.800.323.4576

www.honeywell.com

NOTE: Honeywell reserves the right, without notification, to make changes in product design or specifications.

HSV-VMSSERV-01-US(1019)DS-Z
© 2019 Honeywell International Inc.

**THE
FUTURE
IS
WHAT
WE
MAKE IT**

Honeywell