

### ADI Ordering Information



### PR-1-090

#### Cotag 090 Mullion Reader

6" (15.24cm) read range, mullion mount, two stage unit. Requires 12VDC (HPS123) linear power supply. Uses the PX-1-C active Cotag proximity card. Dimensions: 2.7" H x 1.8" W x 0.6" D (6.8cm H x 4.6cm W x 1.5cm D).



### PR-1-280

#### Cotag 280 Prox Reader

30" (76.2cm) read range, surface mount, red/yellow/green LED's, two stage unit for exterior or interior applications. Requires 12VDC (HPS123) linear power supply. Uses the PX-1-C active or PX-1-CP passive Cotag proximity card. Dimensions: 10.25" H x 8.6" W x 1.0" D (26cm H x 22cm W x 2.5cm D).



### PR-5311-C

#### Controller for Cotag 280/090 Readers



### C940

#### Cotag Wrist Tag

Lightweight grey proximity Cotag designed to fit on wrist strap. AD/ND functionality for use with access control systems. Dimensions: 1.61" H x 1.53" W x .7" D (4.1cm H x 3.9cm W x 1cm D).



### C940-S

#### Cotag Wrist Strap

Cotag wrist strap used with the C940 wrist tag.



### C970

#### Vehicle Tag



### PX-1-C

#### Cotag Prox Card, Active (32-Bit)

Active Cotag proximity card. Cards are slot punched on short side for badge clips (BC-1) and are compatible with the PR-1-090 and PR-1-280 proximity readers. Dimensions: 2.125" H x 3.375" T (5.398cm H x 8.573cm T).



### PX-1-C/PLAIN

#### Cotag Prox Card, No Logo (32-Bit)

Active Cotag proximity card with no logo. Cards are slot punched on the short side and are compatible with the PR-1-090 and PR-1-280 proximity readers. Dimensions: 2.125" H x 3.375" T (5.398cm H x 8.573cm T).



### PX-KEY-C

#### Cotag Proximity Key Tag

Lightweight black proximity Cotag suitable for attaching to a keyring. Dimensions: 1.22" H x 1.93" W x .37" T (3.1cm H x 4.9cm W x .95cm T).

### OMNICLASS™

Honeywell's new OmniClass™, contactless smart card family is based on 13.56MHz technology. The OmniClass family's encryption provides more security than standard 125kHz proximity. The OmniClass readers support ISO 14443A, 14443B and 15693, although the reader may only be able to read the card serial number on some cards. OmniClass credentials that are 16K can also store data for other applications, allowing campuses and other facilities to issue a single card. OmniClass credentials include multi-technology cards with OmniClass, HID prox and/or magnetic stripe.

#### OM30BHONA

##### OmniClass Mullion Reader, Black

Black-colored, Honeywell OmniClass, mullion-style smart card reader with 18" pigtail wire connection. Compatible with OmniClass and iCLASS credentials. Up to 3.0" (7.6cm) read range. Requires 10-16VDC linear power supply. Current requirements: 65mA average, 225mA peak. Dimensions: 4.04" H x 1.90" W x .80" D (10.26cm H x 4.83cm W x 2.03cm D).



#### ADI Ordering Information



#### OM40BHONA

##### OmniClass US Gang Reader, Black

Black-colored, Honeywell OmniClass, US gangbox-style smart card reader with 18" pigtail wire connection and magnetic tamper. Compatible with OmniClass and iCLASS credentials. Up to 4.5" (11.4cm) read range. Requires 10-16VDC linear power supply. Current requirements: 80mA average, 260mA peak. Dimensions: 4.80" H x 3.30" W x .85" D (12.19cm H x 8.38cm W x 2.16cm D).



#### OM45BHONA

##### OmniClass UK/Asian Gang, Black

Black-colored, Honeywell OmniClass, UK/Asian gangbox-style smart card reader with 18" pigtail wire connection and magnetic tamper. Compatible with OmniClass and iCLASS credentials. Up to 3.0" (7.6cm) read range. Requires 10-16VDC linear power supply. Current requirements: 80mA average, 260mA peak. Dimensions: 3.30" H x 3.30" W x .75" D (8.38cm H x 8.38cm W x 1.91cm D).



#### OM55BHONA

##### OmniClass Keypad RDR, Black

Black-colored, Honeywell OmniClass, keypad smart card reader with 18" pigtail wire connection and magnetic tamper. Compatible with OmniClass and iCLASS credentials. Up to 4.0" (10.1cm) read range. Requires 10-16VDC linear power supply. Current requirements: 72mA average, 244mA peak. Dimensions: 4.80" H x 3.30" W x .90" D (12.19cm H x 8.38cm W x 2.29cm D).

