


NR-5

Wide Gap Magnetic Stripe Reader, Track 2


ISO track 2 magnetic stripe card reader for interior or exterior use. Supports NC format 32-bit Wiegand and ABA track 2 encoding (consult factory for special configurations when using existing ABA encoded cards). Tri-color LED indication and fully encapsulated construction. Operating temperature range: -22° to 131° F (-30° to 55° C). Dimensions: 4.52" H x 1.8" W x 1.56" D (11.3cm H x 4.5cm W x 3.9cm D).



NR-2-WR

Exterior/Interior Magnetic Stripe Reader, Track 1

Track 1 magnetic stripe card reader for interior or exterior use. Metal construction (cast zinc) for heavy duty applications. Surface mount. Supports NC format 32-bit Wiegand and ABA track 1 encoding (consult factory for special configurations when using existing ABA encoded cards). Dimensions: 1.5" H x 1.6" W x 6.25" D (3.9cm H x 4.0cm W x 16cm D). Operating temperature range: -40° to 185° F (-40° to 85° C).



MAGNETIC STRIPE CREDENTIALS

NC-2

NC Magnetic Stripe Card (32-Bit)

Magnetic stripe cards with 32-bit NC encoding. Designed to work with the NR-5 magnetic stripe readers. Encoded on high-energy magnetic stripe for long life. Includes hot stamp number equal to encoded number. Dimensions: 2.125" H x 3.375" W x .030" T (5.398cm H x 8.573cm W x .079cm T).



ALSO AVAILABLE:

NC-2-26


Magnetic Stripe Card (26-Bit)

Magnetic stripe card with 26-bit encoding. Designed to work with the NR-5 magnetic stripe readers.

PVC-M-1

Magnetic Stripe Encoded PVC Card with Printed Number (32-Bit)

Plain white PVC high-energy magnetic stripe card. This card can be used with all PVC printers. Dimensions: 2.125" H x 3.375" W x .030" D (5.398cm H x 8.573cm W x .076cm D).



ALSO AVAILABLE:

PVC-M-2

Magnetic Stripe PVC Card, No Hot Stamp (32-Bit)

PVC-M-4

PVC 3 Track Low Coercivity, Not Encoded, Blank

CR-1

Wiegand Swipe Reader, Black

Black Wiegand swipe card reader. Can be used exterior or interior. Surface mount. Compatible with all Wiegand cards except the SC-2-A and NC-1100008. Dimensions: 2.3" H x 5.3" W x 1.7" D (6.0cm H x 13.6cm W x 4.5cm D).




ALSO AVAILABLE:

CR-1B

Wiegand Swipe Reader, Beige

Beige Wiegand swipe card reader. Can be used exterior or interior. Surface mount. Compatible with all Wiegand cards except the SC-2-A and NC-1100008. Dimensions: 2.3" H x 5.3" W x 1.7" D (6.0cm H x 13.6cm W x 4.5cm D).



AR-1

Epic Reader Black

Black ergonomic design Wiegand swipe reader using the same mounting pattern as the HU/W3100340 (standard Wiegand swipe reader). Compatible with all Wiegand cards except the SC-2-A and NC-1100008. Dimensions: 2.63" H x 5.88" W x 1.75" D (6.67cm H x 14.93cm W x 4.45cm D). Operating temperature range: -40° to 158° F (-40° to 70° C).



CI-1

Wiegand Insertion Reader


Wiegand insertion card reader. Can be used exterior or interior. Flush mount on a triple gang box using mounting plate (CI-MP). Compatible with all Wiegand cards except the SC-2-A and NC-1100008. Dimensions: 2.0" H x 3.2" W x 3.0" D (5.1cm H x 8.2cm W x 7.6cm D).



SC-2

Wiegand Card, Hot Stamp (26-Bit)

Wiegand 26-bit NC format card with printed number on card equal to encoded number. Compatible with all Wiegand readers except the CI-2 or NC-2802001. SC-2 cards feature Northern artwork and logo. Dimensions: 3.375" H x 2.125" W (8.573cm H x 5.398cm W).



ALSO AVAILABLE:

SC-1


Wiegand Card, No Hot Stamp (26-Bit)

Wiegand 26-bit NC format card with no numbers stamped on card. Compatible with all Wiegand readers except the CI-2 or NC-2802001. SC-1 cards feature Northern artwork and logo. Dimensions: 3.375" H x 2.125" W (8.573cm H x 5.398cm W).

PVC-W-3

Wiegand PVC Card, 2 Side Printable, Glossy (26-Bit)

Wiegand card (26-bit) with two glossy sides to print on using the PVC printer (can be used with all PVC printers). No hot stamped number. Compatible with all Wiegand readers except the CI-2. Dimensions: 3.375" H x 2.125" W (8.573cm H x 5.398cm W).



ALSO AVAILABLE:

PVC-W-4

Wiegand/Magnetic Stripe Card, 1 Side Printable, Hot Stamp, Glossy (26-Bit)

Wiegand card (26-bit) with one glossy side to print on using the PVC printer (can be used with all PVC printers). Printed number on card equals the encoded number. Compatible with all Wiegand readers except the CI-2. Dimensions: 3.375" H x 2.125" W (8.573cm H x 5.398cm W).

