

The Securit is the perfect solution for residential and light commercial applications with a touch of class.

PANELS



ST800L

Securit800L Panel

- 8 Zones, 6 Programmable for: Alarm, Entry/Exit, Access (walk through), Personal Attack, Part Set Entry, Part Set Isolation.
- 1 Programmable for: Entry, Alarm, Fire, Keyswitch.
- 1 Fixed: Entry/Exit.
- Home Set Facility: Gives flexibility by automatically isolating pre-programmed zones, allowing the system to be armed while the User remains inside.
- Manual Isolation: The system can be tailored for any situation that arises by isolating individual zones which have not been programmed for Home or Part Set Isolation.
- Remote P.A. option: The Remote keypads can be programmed to give a Personal Attack Feature, using the * and # Keys.
- Extension Speaker Output: For greater enhanced sounds, up to two 16 Ohm extension speakers can be fitted.
- Chime Function: Enabling this feature allows Monitoring of chosen zones while the panel is disarmed.
- Two User Codes: Main User code plus second code for children or cleaner etc.

ST800L-PCB

PCB only



ST802

Securit 802 panel with integral keypad

The perfect solution for residential and light commercial applications with a touch of class

This 8-zone control unit is designed with the needs of both the engineer and the end-user in mind.

- Eight hardwired zones of which 7 zones are programmable, plus tamper zone.
- Sleek design; complete with an integral keypad, so that it will blend into most environments.
- Easy to operate; the back-lit keypad is simple to use and provides a positive tactile and audio response giving confidence in operation.
- It incorporates the ability to add up six optional pocket sized remote LED keypads in case additional setting points are required.
- Full set, night set and home set options provided to simplify operation and match user operational needs.

ST802L-PCB

PCB only



ST800L-UI

User LED keypad for ST800L

- Maximum Number Allowed: Six
- Supply Voltage: 12V
- Quiescent Current: 20 mA.
- Active: 45 mA.
- Dimensions: 70mm x 120mm x 25mm (h x w x d)
- Weight: 0.13 Kg
- Approvals: CE Designed to comply with BS4737 Part I.

ACCESSORIES

CAB=6/1

Cable – 6 Core

CAB=8/1

Cable – 8 Core

DOCBOX

Document Box C/W Blank LI