

# Access 8 CM Pin t

a reliable pin pad reader

Access 8 CMpin t improves security in access control by providing pin code identification to be used together with an identification card. The keypad of the reader is based on EMFi foil technology. There are no moving parts in the pin pad, and due to this no maintenance is required. The foil as well as the electrical parts of the reader are cast in epoxy and are therefore safe from damage inside the reader.

Access 8 CMpin t is vandal resistant and can be installed directly onto a metal surface without any insulation. The unique design of the housing guarantees that the reader can be used in the most demanding surroundings. Good performance and robustness ensure optimal functionality even in harsh environments.

Access 8 CMpin reads compatible application specific data from one selected sector of the Mifare® Standard transponders and supports also Mifare® Multi-application transponders. A configuration card defined by Idesco or the customer can be used in programming the required reader output, application specific keys as well as the sector to be read. Also the required data length can be defined according to individual application demands. In case there is no sector coding on the card, the reader reads the serial number of the card. The pin code length can be sent out in 4 or 8 bit format.

Access 8 CMpin t offers multiple and advanced options for reader configuration.

There are several colour options for the housing, but the stock colours are black and grey. Lenses are available as black and white. The Access 8 CMpin (t) reader is also available with customer logo. The design of the readers is protected by international registration.



## Specifications

Voltage	24 V (+10...+30 V)
Current consumption	130 mA
Interfaces:	Wiegand RS232 Clock and Data
Data length	Adjustable
Material of design housing	Plastic
Dimensions of housing (hwxwd)	138 x 44 x 24 mm
Operating temperature	-40...+55 °C
Storage temperature	-40...+55 °C
Protection class	IP47
Cable	LIYY 3 m
Led	Tricolor
Buzzer control	cable
Carrier frequency	13.56 MHz
Field strength	According to EN300330
EMC	Meets CE requirements

Idesco Oy reserves the right to revise this publication and to make changes to its content as well as the right to change or discontinue these products, at any time, without obligation to notify any person or entity of such revisions or changes. All trademarks and registered trademarks are property of their respective owners. Printed in Finland 10/2008 C00097E v.1.11