

ICODE Tag Selection

ICODE SLI Card

ICODE 2402 Tag

ICODE Sail Tag

LOGI TAG 161 ICODE SLI

Idesco offers a wide range of 13.56 MHz tags and cards. Typical applications for these products include access control, time and attendance and asset marking. These products are available as a PVC card, as an epoxy laminated coin tag, and as a polycarbonate Sailtag keyring. All these tag types are suitable for indoor and outdoor use. Both card types have good printability with thermal transfer and thermal sublimation printers.



Specifications

	ICODE SLI CARD	ICODE 2402 Tag	ICODE Sail Tag	LOGITAG 161 ICODE SLI
Chip Type	ISO 15693 / ISO 18000-3	ISO 15693 / ISO 18000-3	ISO 15693 / ISO 18000-3	ISO 15693 / ISO 18000-3
Size	Credit card	Diameter 24 mm, thickness 2 mm	56x32x8 mm	Diameter 16 mm, thickness 3 mm
Operating Temperature	-20 ... +50 °C	-20 ... +70 °C	-40 ... +70 °C	-20 ... +70 °C
Storage Temperature	-20 ... +50 °C	-25 ... +85 °C	-40 ... +85 °C	-25 ... +85 °C
Protection Class	IP67	IP 66	IP 68	IP68
Colour	White	White	Black	Grey
Other		Available with a black leather keyfob that can be customer-tailored.		

Idesco Oy reserves the right to revise this publication and to make changes to its content as well as the right to change or discontinue these products, at any time, without obligation to notify any person or entity of such revisions or changes. All trademarks and registered trademarks are property of their respective owners. C00405E v1.00 31.10.2011