

# Alarm Box

## AL-1112

- Supports DirectIP™ NVR
- Supports IDIS Solution Suite
- 4 Relay Output
- 8 Alarm Input
- DC Output for Small Power Devices
- LED Indicator of Alarm Status



### SPECIFICATIONS

INTERFACE	
Alarm Input	8 Digital-Input - Dry contact, Wet contact High : Open or DC 5V ~ DC 30V Low : Short or DC 0V ~ DC 1.8V*
Alarm Output	4 Relay-out - NC, NO, COMMON
Power Output	12VDC(300mA), 5VDC(400mA)
Ethernet	10/100Mbps
DirectIP Supported	Yes
USB	Yes(Spare)
GENERAL	
Dimension (W x H x D)	200mm x 44mm x 153mm (7.9" x 1.7" x 6.0")
Unit Weight	0.77kg (1.7lb)
Operating Temperature	-10°C ~ +50°C (+14°F ~ +122°F) *Starting up at above 0°C (32°F)
PoE(class)	Yes(IEEE 802.3at Class 4)
Power source	12VDC, 24VAC, PoE
Power Consumption	12V=, 2.19A, 26.3W 24V=, 1.57A, 22.9W, 50/60Hz PoE, IEEE 802.3at(Class 4), 23W
Approvals	FCC, CE, KC

### DIMENSIONS

(Unit - mm)

