

Full HD IR Dome Camera

DC-D2212R

- Easy installation with DirectIP NVR
- Full HD (1080p) resolution
- Fixed Lens (f=4.0mm)
- micro SD/SDHC
- PoE(IEEE 802.3af class 2), 12V DC
- Day&night (ICR)
- IR LED (Distance : 15m)
- 3-axis mechanical design for installation
- Supports ONVIF



SPECIFICATIONS

VIDEO																																																																				
Image Sensor	1/2.9" CMOS																																																																			
Max. Resolution	1920 x 1080																																																																			
Scanning Mode	Progressive Scan																																																																			
Lens type	Fixed-focal																																																																			
Focal Length	f=4.0mm																																																																			
Aperture	F2.0																																																																			
Iris Control	Fixed Iris																																																																			
Angular Field of View	84.4°(H), 50.3°(V), 104.6°(D)																																																																			
Pan/Tilt Range	Pan: -180° ~ 174°, Tilt: 0° ~ 65°																																																																			
Min. Illumination	COLOR : 0.07 lux @F2.0 B/W : 0 lux (IR LED ON)																																																																			
S/N Ratio	31.2dB																																																																			
Dynamic Range	74.7dB																																																																			
Electronic Shutter Speed	Auto / Manual (1/30 ~ 1/8000), Anti-Flicker, Slow Shutter(1/7.5,1/15)																																																																			
Day & Night	IR cut filter with auto switch																																																																			
IR Distance (LEDs)	15m (2ea)																																																																			
Image Setting	Configurable Exposure, White Balance, Sharpness																																																																			
Digital Noise Reduction	Configurable 2DNR																																																																			
Backlight Compensation	On / Off / HSBC																																																																			
Image Stabilizer	-																																																																			
Privacy Masking	16 Zones																																																																			
Intelligent Video	Video Motion Detection, Active Tampering Alarm, Trip Zone																																																																			
Video Out	1 BNC(Accessory)																																																																			
NETWORK																																																																				
	<table border="1"> <thead> <tr> <th>DirectIP Mode</th> <th>Compatibility Mode</th> </tr> </thead> <tbody> <tr> <td>Video Compression</td> <td>H.264(MP), M-JPEG</td> </tr> <tr> <td>Bitrate Control</td> <td>H.264 - CBR / VBR</td> </tr> <tr> <td>Max. Frame Rate</td> <td>30fps : 1920 x 1080</td> </tr> <tr> <td>Audio Compression</td> <td>-</td> </tr> <tr> <td>Two-way audio</td> <td>-</td> </tr> <tr> <td>IP Camera Protocol</td> <td>DirectIP</td> </tr> <tr> <td rowspan="2">Supported Resolution</td> <td>1920x1080, 1280x720,</td> </tr> <tr> <td>704x480, 640x360, 352x240</td> </tr> <tr> <td rowspan="2">Multi-Video Streaming</td> <td>Quadruple streaming</td> </tr> <tr> <td>Triple streaming</td> </tr> <tr> <td rowspan="2">Network Protocols</td> <td>Direct IP Protocol</td> </tr> <tr> <td>RTP/RTSP/TCP, RTP/RTSP/HTTP/TCP, RTP/UDP RTSP/TCP, HTTP, HTTPS, FTP, SNTP, SMTP, FEN, mDNS, uPNP</td> </tr> <tr> <td>Security</td> <td>SSL Encryption</td> </tr> <tr> <td>Remote Access Client</td> <td>DirectIP™ NVR connection</td> </tr> <tr> <td>Ethernet</td> <td>RJ45(10/100BASE-T)</td> </tr> <tr> <td>Edge Storage</td> <td>micro SD/SDHC</td> </tr> <tr> <th colspan="2">ALARM & EVENT</th> </tr> <tr> <td>Trigger Event</td> <td>Motion Detection, Tampering, TripZone</td> </tr> <tr> <td>Event Buffering (Pre & Post)</td> <td>yes (up to 60MB)</td> </tr> <tr> <td>Event Notification</td> <td>Remote S/W, Email (with Image)</td> </tr> <tr> <td>Audio In/ Out</td> <td>-</td> </tr> <tr> <td>Alarm In/ Out</td> <td>-</td> </tr> <tr> <th colspan="2">ENVIRONMENTAL</th> </tr> <tr> <td>Vandal-proof Casing</td> <td>-</td> </tr> <tr> <td>Out-door Ready</td> <td>-</td> </tr> <tr> <td>Operating Temperature</td> <td>-10°C ~ +50°C (+14°F ~ +122°F) *Starting up at above 0°C (32°F)</td> </tr> <tr> <td>Operating Humidity</td> <td>0% ~ 90%</td> </tr> <tr> <th colspan="2">ELECTRICAL</th> </tr> <tr> <td>Power Source</td> <td>12VDC, PoE(IEEE 802.3af class 2)</td> </tr> <tr> <td>Power Consumption</td> <td>3.96W</td> </tr> <tr> <td>Approvals</td> <td>FCC, CE(50130-4), KC</td> </tr> <tr> <th colspan="2">MECHANICAL</th> </tr> <tr> <td>Dimensions</td> <td>Ø131 x 75.8mm (Ø5.16" x 2.99")</td> </tr> <tr> <td>Weight</td> <td>0.3 kg (0.66 lb)</td> </tr> </tbody> </table>	DirectIP Mode	Compatibility Mode	Video Compression	H.264(MP), M-JPEG	Bitrate Control	H.264 - CBR / VBR	Max. Frame Rate	30fps : 1920 x 1080	Audio Compression	-	Two-way audio	-	IP Camera Protocol	DirectIP	Supported Resolution	1920x1080, 1280x720,	704x480, 640x360, 352x240	Multi-Video Streaming	Quadruple streaming	Triple streaming	Network Protocols	Direct IP Protocol	RTP/RTSP/TCP, RTP/RTSP/HTTP/TCP, RTP/UDP RTSP/TCP, HTTP, HTTPS, FTP, SNTP, SMTP, FEN, mDNS, uPNP	Security	SSL Encryption	Remote Access Client	DirectIP™ NVR connection	Ethernet	RJ45(10/100BASE-T)	Edge Storage	micro SD/SDHC	ALARM & EVENT		Trigger Event	Motion Detection, Tampering, TripZone	Event Buffering (Pre & Post)	yes (up to 60MB)	Event Notification	Remote S/W, Email (with Image)	Audio In/ Out	-	Alarm In/ Out	-	ENVIRONMENTAL		Vandal-proof Casing	-	Out-door Ready	-	Operating Temperature	-10°C ~ +50°C (+14°F ~ +122°F) *Starting up at above 0°C (32°F)	Operating Humidity	0% ~ 90%	ELECTRICAL		Power Source	12VDC, PoE(IEEE 802.3af class 2)	Power Consumption	3.96W	Approvals	FCC, CE(50130-4), KC	MECHANICAL		Dimensions	Ø131 x 75.8mm (Ø5.16" x 2.99")	Weight	0.3 kg (0.66 lb)
DirectIP Mode	Compatibility Mode																																																																			
Video Compression	H.264(MP), M-JPEG																																																																			
Bitrate Control	H.264 - CBR / VBR																																																																			
Max. Frame Rate	30fps : 1920 x 1080																																																																			
Audio Compression	-																																																																			
Two-way audio	-																																																																			
IP Camera Protocol	DirectIP																																																																			
Supported Resolution	1920x1080, 1280x720,																																																																			
	704x480, 640x360, 352x240																																																																			
Multi-Video Streaming	Quadruple streaming																																																																			
	Triple streaming																																																																			
Network Protocols	Direct IP Protocol																																																																			
	RTP/RTSP/TCP, RTP/RTSP/HTTP/TCP, RTP/UDP RTSP/TCP, HTTP, HTTPS, FTP, SNTP, SMTP, FEN, mDNS, uPNP																																																																			
Security	SSL Encryption																																																																			
Remote Access Client	DirectIP™ NVR connection																																																																			
Ethernet	RJ45(10/100BASE-T)																																																																			
Edge Storage	micro SD/SDHC																																																																			
ALARM & EVENT																																																																				
Trigger Event	Motion Detection, Tampering, TripZone																																																																			
Event Buffering (Pre & Post)	yes (up to 60MB)																																																																			
Event Notification	Remote S/W, Email (with Image)																																																																			
Audio In/ Out	-																																																																			
Alarm In/ Out	-																																																																			
ENVIRONMENTAL																																																																				
Vandal-proof Casing	-																																																																			
Out-door Ready	-																																																																			
Operating Temperature	-10°C ~ +50°C (+14°F ~ +122°F) *Starting up at above 0°C (32°F)																																																																			
Operating Humidity	0% ~ 90%																																																																			
ELECTRICAL																																																																				
Power Source	12VDC, PoE(IEEE 802.3af class 2)																																																																			
Power Consumption	3.96W																																																																			
Approvals	FCC, CE(50130-4), KC																																																																			
MECHANICAL																																																																				
Dimensions	Ø131 x 75.8mm (Ø5.16" x 2.99")																																																																			
Weight	0.3 kg (0.66 lb)																																																																			

DIMENSIONS

(Unit - mm)



ACCESSORIES(OPTIONAL)



ACCESSORIES CONFIGURATION TREE

