

DC-D4536HRX

5MP Vandal-Resistant IR Dome Camera



- Easy installation with DirectIP NVR
- micro SD/SDHC/SDXC, Smart Failover
- IK10 / IP67
- True wide dynamic range (WDR)
- Supports ONVIF
- 5MP (2592x1944) resolution
- Two-way audio
- PoE (IEEE 802.3af Class 3), 12V DC
- IR LED (30m / 98.4 ft (6ea))
- Motorized Vari-focal lens (f=3.0 - 13.5mm)
- Alarm in / out
- Day and night (ICR)
- 3-axis mechanical design for installation

SPECIFICATIONS

Video	
Image Sensor	1/2.8" CMOS
Max. Resolution	2592 x 1944
Scanning Mode	Progressive Scan
Lens Type	Motorized Vari-focal
Focal Length	3.0 ~ 13.5mm
Aperture	F1.4 ~ 3.2
Iris Control	DC Iris
Angular Field of View	[4:3 mode] Wide : 91°(H) 66°(V) 120°(D) Tele : 31°(H) 23°(V) 38°(D) [16:9 mode] Wide : 91°(H) 49°(V) 107°(D) Tele : 31°(H) 17°(V) 35°(D)
Min. Illumination	COLOR: 0.15 lux @ F1.4 B/W : 0 lux (IR LED ON)
Dynamic Range	120dB (True WDR)
Electronic Shutter Speed	Auto / Manual (1/30 ~ 1/10,000), Anti-Flicker, Slow Shutter (1/7.5, 1/15)
Day and Night	Yes (ICR)
IR Distance (LEDs)	30m / 98.4 ft (6ea)
Image Setting	Exposure, White Balance, Self-Adjusting Video Mode (Sharpness, Contrast, Colors, Brightness Control)
Backlight Compensation	BLC
Mirroring / Pivot	Horizontal / Vertical / Pivot
De-fog	Yes
Privacy Masking	8 Zones
Intelligent Video	Video Motion Detection, Active Tampering Alarm, Trip Zone
Pan/Tilt/Rotate	
Pan Range	-175° ~ 175°
Tilt Range	0° ~ 67°
Rotate Range	-177° ~ 177°
Network	
Video Compression	H.265, H.264 (MP), M-JPEG
Intelligent Codec	Yes
Bitrate Control	H.265 - CBR/ VBR H.264 - CBR/ VBR
Audio Compression	ADPCM 16K, G.726, G.711 u-Law, G.711 a-Law
Two-way Audio	Yes
IP Camera Protocol	DirectIP 2.0, ONVIF Profile S/T
Max. Frame Rate	4:3 mode : 30ips : 2592 x 1944(WDR) 16:9 mode : 30ips : 2592 x 1456(WDR)
Supported Resolution	4:3 : 2592x1944, 1920x1440, 1280x960, 640x480 16:9 : 2592x1456, 1920x1080, 1280x720, 640x360
Multi-video Streaming	Quadruple Streaming
Network Protocols	DirectIP 2.0 Protocol, IPv4, IPv6, RTP/RTSP/TCR/RTSP/HTTP/TCP/RTT/UDP/RTSP/TCP, HTTP/HTTPS/FTP/SNTP/SMTP/FEN mDNS, uPNP, SNMPv2
Security	Digest authentication, Password Protection, User access log, IP Filtering, IEEE802.1X/EP-TLS, Chained Fingerprint, SSLEncryption, HTTPEncryption
Ethernet	RJ45 (10/100BASE-T)
Recording Session Buffer (NLTsrec)	Yes (Up to 60MB)
Edge Storage	micro SD/SDHC/SDXC Smart Failover (Up to 512GB)
Alarm and Event	
Trigger Event	Motion Detection, Alarm in, Audio detection, Tampering, Trip Zone
Event Notification	Remote S/W, Email (with Image)
Audio Alarm	Yes
Audio In / Out	1 / 1
Alarm In / Out	1 / 1
Environmental	
Vandal Proof Casing	IK10
Outdoor Ready	IP67, Heater
Operating Temperature	-40°C ~ +55°C (-40°F ~ +131°F) *Starting up at above -20°C (-4°F)
Operating Humidity	0% ~ 90%
Electrical	
Power Source	12VDC, PoE IEEE802.3af(Class 3)
Power Consumption	12V=, 1.1A, 13.2W PoE IEEE802.3af(Class 3), 11W
Approval	FCC CE UL, KC
Mechanical	
Dimensions	Ø155 x 104.4mm(Ø6.1" x 4.11")
Weight	1kg (2.2lb)



PRODUCT IMAGE



DIMENSIONS



ACCESSORIES (OPTIONAL)

DA-JB2200	DA-MA2100	DA-WM2050	DA-CM2050
JUNCTION BOX	DA-MA2100	WALL MOUNT	CEILING MOUNT
DA-LM2000	DA-RM2000	DA-FM1500	
Pole Mount	Corner Mount	Flush Mount	

ACCESSORY CONFIGURATION BY INSTALLATION ENVIRONMENT

PRODUCT	INSTALLATION ENVIRONMENT	ACCESSORY CONFIGURATION
DC-D4536HRX	WALL	 JUNCTION BOX Model:DA-JB2200
		or
		 DA-MA2100 Model:DA-MA2100
		+
	CELLING	 WALL MOUNT Model:DA-WM2050
		 JUNCTION BOX Model: DA-JB2200
		or
		 DA-MA2100 Model: DA-MA2100
		+
		 CEILING MOUNT Model: DA-CM2050
	POLE	 DA-MA2100 Model: DA-MA2100
		+
		 WALL MOUNT Model: DA-WM2050
		+
	CORNER	 POLE MOUNT Model: DA-LM2000
		 DA-MA2100 Model:DA-MA2100
		+
		 WALL MOUNT Model:DA-WM2050
	ETC	+
		 CORNER MOUNT Model:DA-RM2000
	ETC	 FLUSH MOUNT Model: DA-FM1500