

IR-300



IDIS Security Workstation IR-300 enables to establish satisfying and quick surveillance system with high performance, reliability and manageability.

OS(Operating system) stably installed in SSD and IDIS Solution Suite VMS support wonderful operation up to large systems and ensure important data retention through RAID and Redundant Power.

IR-300 is the perfect product to build powerful and economical surveillance system.

- Pre-installed with IDIS Solution Suite VMS
- Tested and validated with IDIS Solution Suite up to 64 Full HD H.264 / 265 IP cameras
- Storage configuration: 8 SATA + 2 eSATA Ports
- Supports up to 64 Full HD cameras in real-time for enterprise-level surveillance systems
- 400Mbps maximum recording bandwidth per server
- Complete compatibility with IDIS components : IP cameras, analog DVR, DirectCX TVR, DirectIP NVR, and encoders
- 2U rack mount chassis
- Supports H.264, H.265 compression, and Intelligent Codec
- Supports Onvif Profile S, Axis, Panasonic, etc

SPECIFICATIONS

IR-300		
SYSTEM	IDIS Solution Suite	Compatible with Expert and Federation Version 2.8.2 or Higher
	Network Connection	2 GbE RJ-45 Ports (1000Base-T)
	Recording Data Rate	Up to 400Mbps
	Number of Cameras	64Ch Recommended
	Hard Disk Drive Configuration	8 SATA + 3 eSATA, RAID 1, 5, 10 Supported
	SSD	120G SSD for Operating System (M.2 type)
	Operating System	Microsoft® Windows Embedded Standard 8
	Processor	Intel® I7-7700, 3.6GHz
	Memory	DDR4 PC-17000, 16GB
	Video Outputs	1 HDMI, 1 DP, 1 VGA
	USB	6 (2 Front USB 2.0 + 2 Back USB 3.0 + 2 Back USB 2.0)
	RS-232	1 (DB9)
	Optical Drive	-
MECHANICAL	Form Factor	2U Rack Mount Chassis
	Dimensions (W x D x H)	482.6mm x 88mm x 523.5mm (19" x 3.5" x 20.6")
	Weight	23.2lbs (10.5kg)
ELECTRICAL	Power Input	AC 100-240V~, 50/60Hz, 6.0 - 3.0A (Redundant)
	Power Supply	Dual Power (Redundant SMPS)
	Power Consumption	100W
ENVIRONMENTAL	Operating Temperature	0° to 40°C (32° to 104°F)
	Operating Humidity	0% to 90%
ACCESSORIES SUPPLIED	Power Cord	1
GENERAL	Certifications	FCC, CE, CB, UL, PSE

DIMENSIONS

