Reading Range

Frequency

Site Code

Multiple Reading

2.45GHz Long Range Reader



Dual 8bit Microprocessor and ISM Band Receiver

10m

System Features

- · Guarantees Stable Reading Range of 10M
- · Various Applications: Long Range Parking Control, Asset Tracking, Personnel Tracking, Logistics/Fleet Management and etc.
- · Multiple Card Identification (30 Tags / Sec)
- · 90° One-Directional Antenna Suitable for Vehicle Management (360° Omni-Directional Antenna Optional)
- \cdot Encrypted tag ID and Secure Protocols Between Readers and Tags
- · Automatic Site Code Setting via 256 Communication Channels
- · Configurable Site Code
- · Prohibits Multiple Card Identification Error (HOLD Control Input)
- · Prevention of Repeated Card Identification Error (OTR Mode Input)
- · Direct Bargate Output (Open Collector Output : 1s)
- · Available for Outdoor Installation (Epoxy Molding / Outdoor Capacity: IP66)







Active Good Function Weather Proof











Modulation	Encrypted GFSK
Directivity	90° One-Directional Antenna
	360° Omni-Directional Antenna(Optional/Suitable for Access Control and Personnel Tracking)
Receiver Gain	Over -80dBm
Power / Current	DC12V / Max.50mA
Output Type	26 Bit Wiegand, RS232, Bargate Output
RS232 Type	9,600bps (Parity None, 8 Data Bits, 1 Stop Bit)
Bargate Output	Max.100mA (Open Collector Output : 1s)
OTR (One Time Reading) Input	Low Active Input, DC12V, Max, 50mA Current Drain
HOLD Input	Low Active Input, DC12V, Max. 50mA Current Drain, Vehicle Detector Input
LED Indicator / Buzzer	1 LED Indicator / Piezo Buzzer
Operating Temperature	-35° ~ +65°C
Operating Humidity	10% ~90% Relative Humidity Non-Condensing
Color / Material	Ivory / Polycarbonate, Anodized Aluminum
Dimension (W x H x T)	200 x 200 x 45mm
Weight	1.36kg (Excluding Mounting Bracket)
Certification	FCC, CE, KCC, RoHS

30 Tags / Sec.

256 Site Codes

2.45GHz, ISM Band

Application




Logistics/Fleet Management



Parking Control



Asset Tracking



Personnel Tracking