

IFS Transmission

Power Supplies



OVERVIEW

IFS® offers a broad-range of power supplies for commercial and industrial applications.

These power supplies are available in various configurations, such as wall-mount with exchangeable plug adaptors for flexible global use, desktop “in-line brick style” and DIN-rail for robust industrial applications. These supplies provide a variety of voltage outputs, such as, 5VDC, 12VDC and 24VAC for standard product operation and 48VDC and 56VDC for PoE applications.

Switching supplies include advanced technology and power savings, meeting Level IV (4) and Level V (5) International Efficiency in compliance with California Energy Commission, Energy Star and the EU Code of Conduct for external power supplies. Supplies can be mixed and matched to a variety of IFS transmission products to meet various installation requirements.

STANDARD FEATURES

Voltages

- 5VDC, 12VDC or 24VAC
- 48VDC and 56VDC for PoE devices

Form-factors

- Wall-mount
- Desktop (in-line brick)
- DIN-Rail mount

Applications

- For use with IFS Transmission fiber modules, network switches and media converters
- Commercial or Industrial-grade
- Models for meeting world-wide power requirements

Regulatory Certifications

- UL approved
- CSA approved
- Level IV and V International Efficiency compliant

Warranty

- Two-year warranty

Specifications

IFS Standard Power Supplies

Part Number	Input Voltage	Frequency Range	Output Voltage	Amperage	Type	Dimensions	Weight	Power Level**	Certifications
5VDC Power Supplies (For use with IFS MCR Series Media Converters)									
PS5VDC2A-US	90AC-264AC	47-63Hz	5VDC	2 amp	In Wall	2.9 x 2.6 x 1.3 in. (72.5 x 65.7 x 33.6 mm)	.24 lbs. (110g)	Level 4	EMI Requirements: CISPR 22 Class B, EN55022 Class B, EN61204-3 Class B, VCCI Class B, FCC parts 15 Class B, BSMI; EMS Requirements: EN55024, IED61000-4-2, IEC-61000-4-3, IEC 61000-4-4, IEC-6100-4-5, IEC-61000-4-6, IEC-61000-4-8, IEC-61000-4-11; Safety Requirements: IEC 60950, EN60950-1: CE, TUV, Efficiency Level IV
PS5VDC2A-EU	90AC-264AC	47-63Hz	5VDC	2 amp	In Wall	2.9 x 2.6 x 1.3 in. (72.5 x 65.7 x 33.6 mm)	.24 lbs. (110g)	Level 4	
PS5VDC2A-UK	90AC-264AC	47-63Hz	5VDC	2 amp	In Wall	2.9 x 2.6 x 1.3 in. (72.5 x 65.7 x 33.6 mm)	.24 lbs. (110g)	Level 4	
PS5VDC2A-AUS	90AC-264AC	47-63Hz	5VDC	2 amp	In Wall	2.9 x 2.6 x 1.3 in. (72.5 x 65.7 x 33.6 mm)	.24 lbs. (110g)	Level 4	
PS5VDC25W	90AC-264AC	47-63Hz	5VDC	5 amp	Brick	4.9 x 2 x 1.24 in. (125 x 50 x 91.31.5 mm)	.46 lbs. (208g)	Level 5	
12VDC Power Supplies (For use with IFS Fiber modules, media converters and switches)									
PS12VDC1.5A-U*	100-240VAC	50-60Hz	12VDC	1.5 amp	In Wall	1.7 x 1.4 x 2.9 in. (43.5 x 35.3 x 74 mm)	.23 lbs. (105g)	Level 5	61000-4-4, IEC-6100-4-5, IEC-61000-4-6, IEC-61000-4-8, IEC-61000-4-11; Safety Requirements: IEC 60950, EN60950-1: CE, TUV, Efficiency Level IV
24VAC Power Supplies (For use with IFS Fiber modules and media converters)									
PS24VAC.6-US	120AC	60Hz	24VAC	600ma	In Wall	3.2 x 2.3 x 1.9 in. (81.6 x 58.7 x 48.7 mm)	1.2 lbs. (544g)	Level 4	TUV test to EN60950-1:2006. UL Listed as EPBU.E194233
PS24VAC.6-EU	230AC	50Hz	24VAC	600ma	In Wall	3.2 x 2.3 x 1.9 in. (81.6 x 58.7 x 48.7 mm)	1.4 lbs. (635g)	Level 4	
PS24VAC.6-UK	230AC	50Hz	24VAC	600ma	In Wall	3.2 x 2.3 x 1.9 in. (81.6 x 58.7 x 48.7 mm)	1.4 lbs. (635g)	Level 4	
PS24VAC.6-AUS	230AC	50Hz	24VAC	600ma	In Wall	3.2 x 2.3 x 1.9 in. (81.6 x 58.7 x 48.7 mm)	1.4 lbs. (635g)	Level 4	
613P***	100-240VAC	50-60Hz	13.5VDC	1.3 amp	Brick	1.3 x 2.4 x 4.2 in. (32 x 62 x 106 mm)	.79 lbs. (360g)	Level 5	

IFS PoE Power Supplies

Part Number	Input Voltage	Frequency Range	Output Voltage	Amperage	Type	Dimensions	Weight	Power Level**	Certifications
48VDC Power Supplies (For use with IFS single-port PoE-af Injectors)									
PS48VDC.38A-US	90AC-264AC	47-63Hz	48VDC	380ma	In Wall	.35 x 2.8 x 1.4 in. (8.85 x 69.9 x 35 mm)	.24 lbs. (110g)	Level 4	EMC: CISPR 22 Class B, EN55022 Class B, EN61204-3 Class B, FCC parts 15 Class B, BSMI; EMS Requirements: EN55024, IEC-61000-4-2, IEC-61000-4-3, IEC-6100-4-4, IEC-61000-4-5, IEC-6100-4-6, IEC-61000-4-8, IEC-61000-4-11; Safety Requirements: IEC 60950, UL 60950-1TUV, Efficiency Level IV
PS48VDC.38A-EU	90AC-264AC	47-63Hz	48VDC	380ma	In Wall	.35 x 2.8 x 1.4 in. (8.85 x 69.9 x 35 mm)	.24 lbs. (110g)	Level 4	
PS48VDC.38A-UK	90AC-264AC	47-63Hz	48VDC	380ma	In Wall	.35 x 2.8 x 1.4 in. (8.85 x 69.9 x 35 mm)	.24 lbs. (110g)	Level 4	
PS48VDC.38A-AUS	90AC-264AC	47-63Hz	48VDC	380ma	In Wall	.35 x 2.8 x 1.4 in. (8.85 x 69.9 x 35 mm)	.24 lbs. (110g)	Level 4	
48VDC Power Supplies (For use with IFS 4-port PoE-af injectors)									
PS48VDC65W-US	90AC-264AC	47-63Hz	48VDC	1.35A	Brick	1.9 x 4.5 x 1.2 in. (49 x 115 x 30 mm)	.45 lbs (204g)	Level 5	EMC: CISPR 22 Class B, EN55022 Class B, EN61204-3 Class B, FCC parts 15 Class B, BSMI; EMS Requirements: EN55024, IEC-61000-4-2, IEC-61000-4-3, IEC-6100-4-4, IEC-61000-4-5, IEC-6100-4-6, IEC-61000-4-8, IEC-61000-4-11; Safety Requirements: IEC 60950, UL 60950-1TUV, Efficiency Level V
PS48VDC65W-EU	90AC-264AC	47-63Hz	48VDC	1.35A	Brick	1.9 x 4.5 x 1.2 in. (49 x 115 x 30 mm)	.45 lbs (204g)	Level 5	
PS48VDC65W-UK	90AC-264AC	47-63Hz	48VDC	1.35A	Brick	1.9 x 4.5 x 1.2 in. (49 x 115 x 30 mm)	.45 lbs (204g)	Level 5	
PS48VDC65W-AUS	90AC-264AC	47-63Hz	48VDC	1.35A	Brick	1.9 x 4.5 x 1.2 in. (49 x 115 x 30 mm)	.45 lbs (204g)	Level 5	

IFS PoE Power Supplies (cont.)

Part Number	Input Voltage	Frequency Range	Output Voltage	Amperage	Type	Dimensions	Weight	Power Level**	Certifications
48VDC DIN-Rail Industrial Power Supplies (For use with IFS multi-port Industrial PoE-af/at media converters and switches)									
PS48VDC100W-DIN	90AC-264AC	47-63Hz	48VDC	2 amp	DIN-Rail	2.2 x 3.5 x 3.9 in. (55 x 90 x 100 mm)	.93 lbs. (420g)	Level 5	EMC: CISPR 22 Class B, EN55022 Class B, EN61204-3 Class B, FCC parts 15 Class B, BSMI: EMS Requirements: EN55024, IEC-61000-4-2, IEC-61000-4-3, IEC-6100-4-4, IEC-61000-4-5, IEC-6100-4-6, IEC-61000-4-8, IEC-61000-4-11: Safety Requirements: IEC 60950, UL 60950-1TUV, Efficiency Level V
PS48VDC240W-DIN	90AC-264AC	47-63Hz	48VDC	5 amp	DIN-Rail	2.5 x 4.9 x 4.5 in. (63 x 125.2 x 113 mm)	2.27 lbs. (1.03Kg)	Level 5	
PS48VDC480W-DIN	90AC-264AC	47-63Hz	48VDC	10 amp	DIN-Rail	3.37 x 4.9 x 5 in. (85.5 x 125.2 x 128.5 mm)	3.53 lbs (1.6Kg)	Level 5	
48VDC Industrial Power Supplies (For use with IFS multi-port Industrial PoE-af modules) Outdoor Use.									
HLG-240-48	90AC-264AC	47-63Hz	48VDC	5 amp	IP67 for Outdoors	9.61 x 2.67 x 1.54 in.) (244.2 x 68 x 39 mm)	2.87 lbs. (1.3K)	Level 5	EMC: CISPR 22 Class B, EN55022 Class B, EN61204-3 Class B, FCC parts 15 Class B, BSMI: EMS Requirements: EN55024, IEC-61000-4-2, IEC-61000-4-3, IEC-6100-4-4, IEC-61000-4-5, IEC-6100-4-6, IEC-61000-4-8, IEC-61000-4-11: Safety UL1012, CAN/CSA-C22.2 No. 107.1-01,UL8750,CSA C22.2 No. 250.0-08, TUV EN61347-1, EN61347-2-13, UL60950-1, TUV EN60950-1, IP67, J6134701, J61347-2-13.
56VDC Power Supplies (For use with IFS single channel PoE-at modules)									
PS56VDC65W-US	90AC-264AC	47-63Hz	56VDC	1.16A	Brick	1.9 x 4.5 x 1.2 in. (49 x 115 x 30 mm)	.45 lbs (204g)	Level 5	EMC: CISPR 22 Class B, EN55022 Class B, EN61204-3 Class B, FCC parts 15 Class B, BSMI: EMS Requirements: EN55024, IEC-61000-4-2, IEC-61000-4-3, IEC-6100-4-4, IEC-61000-4-5, IEC-6100-4-6, IEC-61000-4-8, IEC-61000-4-11: Safety Requirements: IEC 60950, UL 60950-1TUV, Efficiency Level V
PS56VDC65W-EU	90AC-264AC	47-63Hz	56VDC	1.16A	Brick	1.9 x 4.5 x 1.2 in. (49 x 115 x 30 mm)	.45 lbs (204g)	Level 5	
PS56VDC65W-UK	90AC-264AC	47-63Hz	56VDC	1.16A	Brick	1.9 x 4.5 x 1.2 in. (49 x 115 x 30 mm)	.45 lbs (204g)	Level 5	
PS56VDC65W-AUS	90AC-264AC	47-63Hz	56VDC	1.16A	Brick	1.9 x 4.5 x 1.2 in. (49 x 115 x 30 mm)	.45 lbs (204g)	Level 5	

*Uses five different interchangeable power prongs to adapt to most power sockets world wide.

SAA: China/Australia, **UL:** North America/Japan/Parts of China, **CCC:** Parts of China, **VDA:** Europe/Parts of South America, **UK:** United Kingdom/Hong Kong/Singapore.

**Meets Level IV International Efficiency in compliance with California Energy Commission, Energy Star and the EU Code of Conduct for external power supplies.

***Connects to standard wall outlet with IEC line cord

IFS Transmission

Power Supplies

North America
T 855-286-8889

Latin America
T 561-998-6114



interlogix.com

Specifications subject to change without notice.

© 2013 United Technologies Corporation.

All rights reserved.

Interlogix is part of UTC Building & Industrial Systems,
a unit of United Technologies Corporation.

312-3762 2013/12 (76700)