

Essentials

IP Indoor Mini-Dome Camera



Features That Make a Difference:

- 1 and 2 megapixels
- H.264 and MJPEG dual-stream encoding
- Maximum 30 ips
- Multiple remote monitoring options
- 3.6mm fixed lens
- PoE
- Soft Day/Night
- Wide Dynamic Range

The Illustra Essentials Indoor Mini-Domes are available in 1 and 2 megapixel options. With features such as Soft Day/Night and Wide Dynamic Range, these indoor mini-domes can capture video in various lighting conditions. These cameras are easy to install and fit a variety of indoor applications such as retail stores and offices.

Low Light Clarity

The Illustra Essentials Indoor software day/night Mini-Dome cameras master low-light clarity, through a combination of the latest technology in sensor sensitivity and camera processing, delivering clear images both day and night.

The megapixel camera coupled with the megapixel lens create a great low-light performance and clear images ensure that the bandwidth usage and storage costs are kept to a minimum, increasing the cameras impact on the site as well as reducing the total cost of ownership.

Wide Dynamic Range

For applications where challenging lighting conditions are present the Illustra Essentials' WDR takes advantage of the latest pixel-by-pixel dynamic range technology. This is particularly important for strongly backlit scenes such as looking outside from reception areas or corridors which are illuminated through the windows and by indoor lighting revealing whole scene clarity such as faces in detail.

Specifications




	1MP	2MP
Camera		
Imager	1/4"	1/3"
Resolution	1280 x 720	1920 x 1080
Shutter Speed	Auto/manual, 1/3(4) – 1/10000s	Auto/manual, 1/3(4) – 1/10000s
Minimum Illumination	Colour: 0.1Lux/F1.2	Colour: 0.1Lux/F1.6
S/N Ratio	More than 50dB	More than 50dB
Analogue Video Output	N/A	N/A
Camera Features		
IR Illuminator	N/A	N/A
Day/Night	Auto(Electronic)/Colour/B/W	Auto(Electronic)/Colour/B/W
Backlight Compensation	Yes	Yes
Wide Dynamic Range	WDR	WDR
White Balance	Auto/Manual	Auto/Manual
Gain Control	Auto/Manual	Auto/Manual
Digital Noise Reduction	3D	2D
Privacy Zones	Up to 4 areas	Up to 4 areas
Lens		
Focal Length	3.6mm Fixed	3.6mm Fixed
Max Aperture	F1.8	F1.6
Focus Control	Manual	Manual
Angle of View	H: 70°	H: 71.9°
Video		
Video Compression	H.264/MJPEG	H.264/MJPEG
Resolutions	720p (1280 x 720); D1 (704 x 576/704 x 480); CIF (352 x 288/352 x 240)	1080p (1920 x 1080); 720p (1280 x 720); D1 (704 x 576/704 x 480) CIF (352 x 288/352 x 240)
Max Frame Rate	Main Stream: 720p (30ips); Sub Stream: D1/CIF (30ips)	Main Stream: 1080p/720p (30ips); Sub Stream: D1/CIF (30ips)
Audio	N/A	N/A
Network		
Ethernet	RJ-45 (10/100Base-T)	RJ-45 (10/100Base-T)
Wi-Fi	N/A	N/A
Supported Protocols	IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS, Bonjour	IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS, Bonjour
ONVIF-compliant	ONVIF Profile S	ONVIF Profile S
Auxiliary Interface		
Onboard Storage	N/A	N/A
Alarm Input/Output	N/A	N/A
General		
Power Supply	DC12V, PoE (802.3af)	DC12V, PoE (802.3af)
Power Consumption	<1.5W	Max 3W
Operating Temperature	-30°C to +60°C	-30°C to +60°C
IP Rating	N/A	N/A
Vandal Resistant	N/A	N/A
Dimensions	110mm x 54mm	110mm x 54mm
Menu Languages	Chinese (simplified), English (default), French, German, Portuguese, Spanish	English (default), French, German, Portuguese, Spanish
Weight	0.2kg	0.39kg

Model	Description
IES01CFACWSY	Illustra Essentials 1MP mini-dome, 3.6mm, indoor, nonvandal, clear, white, SDN, WDR
IES02CFACWSY	Illustra Essentials 2MP mini-dome, 3.6mm, indoor, nonvandal, clear, white, SDN, WDR

ILLUSTRATE CAMERA MODEL KEY											
ILLUSTRATE SERIES	MODEL	RESOLUTION	FORM FACTOR	LENS	ENVIRONMENT HOUSING	BUBBLE	COLOUR	DAY/NIGHT/IR	WDR	OTHER	
I	E = Essentials	L = Lite	01 = 1MP	B = Bullet	N = None	N = None	N = None	B = Black	C = Colour Only	N = No	A = Hardware Update
	F = Flex	P = Plus	02 = 2MP	C = Compact Dome	F = Fixed	A = Indoor NonVandal	C = Clear	G = Gray	I = TDN w/IR	T = Multi-Exposure (>60 Frames)	
	P = Pro	S = Standard	03 = 3MP	D = Dome	0 = 1.8–3mm	B = Outdoor NonVandal	S = Smoked	S = Silver	S = Soft Day/Night	Y = Yes	
	Q = Edge		05 = 5MP	F = Fisheye	1 = 2.8–12mm	I = Indoor Vandal		W = White	T = TDN		
				M = Mini-Bullet	2 = 3–9mm	O = Outdoor Vandal					
				P = PTZ	3 = 9–22mm						
				W = Wireless Cube	4 = 9–40mm						
				X = Box	5 = 20x						
					6 = 30x						


Optional Mini-Dome Accessories

Model	PFA131
Description	Junction Box
Dimensions	138mm x 42mm
Weight	0.38kg
Load Bearing	3.0kg



Optional Mini-Dome Accessories

Model	PFB200W
Description	Wall Mount
Dimensions	160mm x 120mm x 74mm
Weight	1kg
Load Bearing	1kg



Related Products



VideoEdge



exacqVision



victor

Approvals



www.illustracameras.com