

Features

480p @ 30 fps
1.3 Megapixels @ 15 fps
2.0 Megapixels @ 15 fps
Low-light Performance (0.2 lux)
Power-over-Ethernet
Digital Image Cropping
Motion Detection
Low-power Consumption (<2.8 watts)
Wide Dynamic Range (61 dB)
Network Reliability
Simple Installation

Unique Dome Features

3-axis Gimbal Wall and Pendant Mount Options Extreme Wide and Telephoto Lens Options Megapixel Rated 4.2mm Lens

Available Camera Models

 $IQ040SI-V9-VGA\ Standard\ Camera,\ 30\ fps,\ 0.2\ lux\\ IQ041SI-V10-1.3\ MP\ Resolution\ Standard\ Camera,\ 15\ fps,\ 0.2\ lux\\ IQ042SI-V11-2.0\ MP\ Resolution\ Standard\ Camera,\ 15\ fps,\ 0.2\ lux\\ IQ042SI-V11-2.0\ MP\ Resolution\ Standard\ Camera,\ 15\ fps,\ 0.2\ lux\\ IQ042SI-V11-2.0\ MP\ Resolution\ Standard\ Camera,\ 15\ fps,\ 0.2\ lux\\ IQ042SI-V11-2.0\ MP\ Resolution\ Standard\ Camera,\ 15\ fps,\ 0.2\ lux\\ IQ042SI-V11-2.0\ MP\ Resolution\ Standard\ Camera,\ 15\ fps,\ 0.2\ lux\\ IQ042SI-V11-2.0\ MP\ Resolution\ Standard\ Camera,\ 15\ fps,\ 0.2\ lux\\ IQ042SI-V11-2.0\ MP\ Resolution\ Standard\ Camera,\ 15\ fps,\ 0.2\ lux\\ IQ042SI-V11-2.0\ MP\ Resolution\ Standard\ Camera,\ 15\ fps,\ 0.2\ lux\\ IQ042SI-V11-2.0\ MP\ Resolution\ Standard\ Camera,\ 15\ fps,\ 0.2\ lux\\ IQ042SI-V11-2.0\ MP\ Resolution\ Standard\ Camera,\ 15\ fps,\ 0.2\ lux\\ IQ042SI-V11-2.0\ MP\ Resolution\ Standard\ Camera,\ 15\ fps,\ 0.2\ lux\\ IQ042SI-V11-2.0\ MP\ Resolution\ Standard\ Camera,\ 15\ fps,\ 0.2\ lux\\ IQ042SI-V11-2.0\ MP\ Resolution\ Standard\ Camera,\ 15\ fps,\ 0.2\ lux\\ IQ042SI-V11-2.0\ MP\ Resolution\ Standard\ Camera,\ 15\ fps,\ 0.2\ lux\\ IQ042SI-V11-2.0\ MP\ Resolution\ Standard\ Camera,\ 15\ fps,\ 0.2\ lux\\ IQ042SI-V11-2.0\ MP\ Resolution\ Standard\ Camera,\ 15\ fps,\ 0.2\ lux\\ IQ042SI-V11-2.0\ MP\ Resolution\ Standard\ Camera,\ 15\ fps,\ 0.2\ lux\\ IQ042SI-V11-2.0\ MP\ Resolution\ Standard\ Camera,\ 15\ fps,\ 0.2\ lux\\ IQ042SI-V11-2.0\ MP\ Resolution\ Standard\ Camera,\ 15\ fps,\ 0.2\ lux\\ IQ042SI-V11-2.0\ MP\ Resolution\ Standard\ Camera,\ 15\ fps,\ 0.2\ lux\\ IQ042SI-V11-2.0\ MP\ Resolution\ Standard\ Camera,\ 15\ fps,\ 0.2\ lux\\ IQ042SI-V11-2.0\ MP\ Resolution\ Standard\ Camera,\ 15\ fps,\ 0.2\ lux\\ IQ042SI-V11-2.0\ MP\ Resolution\ Standard\ Camera,\ 15\ fps,\ 0.2\ lux\\ IQ042SI-V11-2.0\ MP\ Resolution\ Standard\ Camera,\ 15\ fps,\ 0.2\ lux\\ IQ042SI-V11-2.0\ MP\ Resolution\ Standard\ Camera,\ 15\ fps,\ 0.2\ lux\\ IQ042SI-V11-2.0\ MP\ Resolution\ Standard\ Camera,\ 15\ fps,\ 0.2\ lux\\ IQ042SI-V11-2.0\ MP\ Resolution\ Standard\ Ca$

IQD40SI-F1 – VGA Dome Camera, 30 fps, 0.2 lux IQD41SI-F1 – 1.3 MP Resolution Dome Camera, 15 fps, 0.2 lux IQD42SI-F1 – 2.0 MP Resolution Dome Camera, 15 fps, 0.2 lux

IQeye 4 Series Dome Accessories

IQD4-WG/IQD4-WB — Wall Mount, Beige or Black IQD4-PG-5/IQD4-PB-5 — Pendant Mount, Beige or Black, 5 Pack IQD4-F2-5/IQD4-F3-5 — Lens Pack, 2.8mm or 8mm, 5 Pack



Camera weight with lens: 9.66oz (274g) without lens: 6.81oz (193g)



Camera weight: 8.8oz (249.5g)

IQeye 4 SeriesHigh-resolution IP Cameras

The IQeye 4 Series cameras deliver IQeye quality IP video in two compact, affordable, and attractive packages. Available from VGA to 2.0 megapixels, the IQeye 4 Series offers high-speed video in a simple, easy to install package. It is 100% Power-over-Ethernet using a single Cat 5 cable for video, power and remote configuration making installation quick and easy.

IQinVision's ultra-stable operating system, bandwidth management tools and image controls deliver outstanding performance you can count on and our non-proprietary open-architecture lets you integrate seamlessly with all the leading network video recording systems.

With versatility for all commercial, retail and residential environments, the IQeye 4 Series makes quality high-definition surveillance a reality.

IQeye 4 Series Dome

NEW!



The versatile IQeye 4 Series Dome camera is designed for discreet indoor use, and works perfectly for ceiling surface mount applications.

An optional mounting accessory kit provides options for wall and pendant mounting.



33122 Valle Road San Juan Capistrano, CA 92675-4853 USA toll-free within U.S. 877.850.0805 phone +1.949.369.8100 fax +1.949.369.8105

© 2009 IQinVision, Inc. 300-2104 Rev. A

www.iqeye.com



IQeye 4 Series

IQeye511 Series

IQeye510 Series