

Traffic Barrier Medium

Access Control | Jacksons Security

Jacksons Fencing
Stowting Common | Ashford | TN25 6BN
www.jacksons-security.co.uk
+44 (0) 1233 750 393

Jacksons
Quality that lasts
Fencing & Access Solutions



Boom joined to cabinet



Boom upright

Standard features include:

- Powder coated cabinet
- Aluminium with red reflectors on boom
- Manual release
- Fixed, pendulum or no support for boom dependant on boom length
- Operating speed of 2 - 12 seconds dependant on boom length

Options include:

- Bottom skirt (up to 9m)
- Boom light
- Boom locking
- Safety photocells
- Articulated arms for restricted headroom applications (up to 5m arm)

When ordering please specify right hand or left hand installation

Jacksons MD 30 barrier

Maximum 240 operations in one hour with a maximum of 5700 per day. Opening time 3 secs

Jacksons MD 45 barrier

Maximum 120 operations in one hour with a maximum of 2800 per day. Opening time 6 secs

Jacksons MD 60 barrier

Maximum 60 operations in one hour with a maximum of 1400 per day. Opening time 12 secs



Traffic Barriers Medium

Specifications and Technical Data

	MD 30	MD 45	MD 60
Control panel	LEO MY D [incorporated]	LEO MY D [incorporated]	LEO MY D [incorporated]
Reversible/irreversible operator	irreversible	irreversible	irreversible
Power supply	230 V- ± 10%, 50Hz single phase	230 V- ± 10%, 50Hz single phase	230 V- ± 10%, 50Hz single phase
Opening or closing time	3 s	6 s	12 s
Manual release	handle	handle	handle
Degree of protection	IP24	IP24	IP24



Boom support arm



Boom Skirt



Jacksons
Quality that lasts
Fencing & Access Solutions