



# MultiCLASS SE Legacy Series

MultiCLASS SE readers with backward compatibility

## MultiCLASS SE legacy adaptable high-frequency access control

Keyscan MultiCLASS SE Legacy is the next generation access control platform that goes beyond the traditional smart card model to offer a secure, standards-based, and flexible platform that has become the new benchmark for highly adaptable interoperable access control solutions.

MultiCLASS SE Legacy readers simplify transition projects from legacy technologies with support for 125 kHz Proximity (Keyscan,

HID and Indala) and provide customers the assurance that their existing investments can be leveraged to enhance their system as business requirements change.

The technology- independent readers also support iCLASS® Seos™ and iCLASS SE credential platforms, as well as standard iCLASS, MIFARE and other leading technologies



### Benefits of Keyscan MultiCLASS SE Legacy platform:

#### Keyscan Elite Key Advantage:

- Keyscan iCLASS ELITE KEY cards and readers feature an added layer of encryption offering additional security to HID's encryption technology. This additional security gives Keyscan access control system users a distinct advantage over public key credentials.

#### Compatibility:

- If you purchased Keyscan iCLASS readers and credentials between June 2005 and November 2013 this legacy product will function with those existing Keyscan Elite Key iCLASS readers and credentials.

#### Easily Interfaced:

- Wiegand output easily interfaces with most existing Wiegand protocol control panels.

#### Security and Functionality:

- iCLASS readers make access control more versatile and offer security through encryption and mutual authentication.
- Supports iCLASS 13.56 MHz smart card technology and can support multiple applications.
- Designed to be compatible with current iCLASS access control environments using existing iCLASS security technology.

### These iCLASS SR credentials are designed to function with Keyscan MultiCLASS SE legacy series readers.

<b>KC2K2SR</b>	iCLASS SR 2K2 Clamshell Card, 36 Bit, Elite Key	<b>KF2K2SR</b>	iCLASS SR 2K2 Smart Fob, 36 Bit, Elite Key
<b>KI2K2SR</b>	iCLASS SR 2K2 ISO Smart Card, 36 Bit, Elite Key	<b>KT2K2SR</b>	iCLASS SR 2K2 Smart Tag, 36 Bit, Elite Key
<b>KI2K2MSR</b>	iCLASS SR 2K2 ISO Smart Card Magstripe, 36 Bit, Elite Key	<b>KTX2ICL</b>	Embedded iCLASS SR 2K2 Transponder, 36 Bit, Elite Key
<b>KI16K16SR</b>	iCLASS SR 16K/16 ISO Smart Card, 36 Bit, Elite Key	<b>TX4ICL</b>	Embedded iCLASS SR 2K2 Transponder, 36 Bit, Elite Key





### How Keyscan MultiCLASS SE Legacy and MultiCLASS SE readers and credentials are designed to work:



# MultiCLASS SE Legacy Series

## MultiCLASS SE readers with backward compatibility

### Specifications:

	KRP10L	KRP15L	KRP40L	KRPK40L
				
Typical read range*	iCLASS SE: 2.6" (6.6 cm)	iCLASS SE: 2.9" (7.4 cm)	iCLASS SE: 3.5" (8.9 cm)	iCLASS SE: 3.3" (8.4 cm)
Mounting	Mini-Mullion Size; physically the smallest iCLASS® readers and are ideally suited for mullion-mounted door installations, U.S. single-gang J-box (with mud ring) or any flat surface		Wall Switch Size; designed to mount and cover single gang switch boxes primarily used in the Americas and includes a slotted mounting plate for European and Asian back box spacing	
Color	Black			
Keypad	No			Yes (4x3)
Dimensions	1.9" x 4.1" x 0.9" 4.8cm x 10.3cm x 2.3cm	1.9" x 6.0" x 0.9" 4.8cm x 15.3cm x 2.3cm	3.3" x 4.8" x 1.0" 8.4cm x 12.2cm x 2.4cm	3.3" x 4.8" x 1.1" 8.5cm x 12.2cm x 2.8cm
Product Weight (Pigtail)	4 oz (114g)	5.2 oz (149g)	7.8 oz (222g)	9.1 oz (258g)
Product Weight (Terminal Strip)	3.0 oz (85g)	4.3 oz (124g)	7.6 oz (216g)	8.0 oz (226g)
Operating Voltage range	5-16 VDC, Linear supply recommended			
Current Draw Standard Power Mode** (mA)	110	120	110	120
Peak Current Draw Standard Power or IPM Mode** (mA)	260	280	265	315
Operating Temperature	-31° to 150° F (-35° to 65° C)			
Storage Temperature	-67° to 185° F (-55° to 85° C)			
Operating Humidity	5% to 95% relative humidity non-condensing			
Transmit Frequency	13.56 MHz & 125 kHz			
13.56 MHz Card Compatibility	Secure Identity Object™ (SIO) on iCLASS® SE/SR™, -ISO14443A (MIFARE) CSN, ISO14443B CSN, ISO15693 CSN			
125 kHz Card Compatibility†	Keyscan, HID, AWID, Indala, EM41-2			
Cable Distance	Wiegand Interface 500ft (150m) (22AWG) - Use Shielded cable for best results			
Panel Connection	Pigtail			
Certifications	UL294/cUL*** (US), FCC Certification (US), IC (Canada), CE (EU)			
Warranty	Limited Lifetime			

\* Typical read range achieved in air. Different types of metal will cause some degradation (typically up to 20%). Use spacers to space product off metal and improve read range if required.

\*\* Measured in accordance with UL294 standards

\*\*\* UL294 functionally certified for Wiegand output only

† If a technology read range is not listed, the compatibility is not currently available in the associated reader model.

© HID Global Corporation. All rights reserved. HID, the HID logo, iCLASS SE, Seos, iCLASS, Secure Identity Object, SIO, Trusted identity Platform, TIP and iCLASS Elite are trademarks or registered trademarks of HID Global in the U.S. and/or other countries.



901 Burns Street East  
Whitby, Ontario, L1N 0E6, Canada  
Toll Free: 1.888.KEYSCAN (Canada/US)  
Tel: +1.905.430.7226  
Web: www.keyscan.ca

KEY 2013-12