

KMP-1216 | MULTIPLEXER



Specifications

General Spec		KMP-1216
Camera	Input	16ports (BNC, CVBS)
	Loop Out	1port (BNC, CVBS)
VCR	Input	16ports (BNC, CVBS)
	Output	16ports (BNC, CVBS)
	Composite	16ports (BNC, CVBS)
Monitor	S-VHS	1port (Mini-Din, S-VHS)
	VGA	1port (DB15-3R, RGB)
Alarm	Input	16ports (DB15-3R, TTL Drive)
	Output	1port (DB15-3R, Dri Contact)
Operating Temperature		-10°C ~ +50°C
Division		4, 8, 9, 10, 13, 16 Division
Power Consumption		20W
Voltage		DC12V 1.5A~18V 1A
Dimension		430(W) × 44(H) × 285(D)
Weight		3Kg

KMP-1209 | MULTIPLEXER



Specifications

General Spec		KMP-1209
Camera	Input	9 ports (BNC,CVBS)
	Loop Out	9 ports (BNC,CVBS)
VCR	Input	1port (BNC, CVBS)
	Output	1port (BNC, CVBS)
Monitor	Composite	3 ports (BNC,CVBS)
	S-VHS	1port (Mini-Din, S-VHS)
	VGA	1port (DB15-3R, RGB)
Alarm	Input	9ports (DB15-3R, TTL Drive)
	Output	1port (DB15-3R, Dri Contact)
Operating Temperature		-10°C ~ +50°C
Division		4, 8, 9, 10, 13, 16 Division
Power Consumption		20W
Voltage		DC12V 1.5A~18V 1A
Dimension		430(W) × 44(H) × 285(D)
Weight		3Kg