

# KSR 8 SERIES

## KSR-816

World's Best Company in Digital Video Recording  
Kodicom provides high quality display pictures with outstanding recording speed.



### Main Functions

- |   |  |   |
|---|--|---|
|  <b>REAL TIME MONITORING</b><br>Simultaneous live images                                   |  <b>COMPACT PICTURE STORAGE</b><br>Images are compressed to an average file size between 2-10Kb per picture using MPEG4 Algorithm |  <b>MULTI SCREEN MONITORING</b><br>1, 4, 9, 16 Split Screen available  |
|  <b>EASY PICTURE RETRIEVAL</b><br>Instant picture retrieval by date/time and camera number |  <b>EVENT CONTROLLED RECORDING</b><br>Reduces the amount of data and automatically records specific events                        | <ul style="list-style-type: none"> <li>• CCTV monitor &amp; PC monitor output</li> <li>• 16 Loop out</li> <li>• 5 Spot out</li> <li>• Convenient archiving using SCSI, IEEE1394, USB2.0 or built-in CD-RW</li> <li>• Instant recording button for all channels with transmission over network</li> <li>• E-mail notification upon alarm, video loss, recording status and more</li> </ul> |
|  <b>REMOTE CONTROL</b><br>Remote Control of PTZ cameras & other electronic devices         |  <b>PICTURE TRANSMISSION OVER NETWORK</b><br>High quality picture transmission over PSTN, ISDN & LAN network                      |   |

Digital Video Recorder(Non-PC based)

# KSR-816

4ch/8ch Model available

### Front/ Rear View

Front




Rear




### Features

- High Quality Realtime Display – Max. 480fps(NTSC) 400fps(PAL)
- High Quality and High Speed Recording – Max. 480fps(NTSC) 400(PAL)
- Various Resolutions on Display and Recording – 704×480, 704×240, 352×240(NTSC), 704×576, 704×288, 352×288(PAL)
- MPEG4
- 1, 4, 9, 16 Division
- Watchdog Function
- Kodicom, Pelco, Dennyard, Bosch, Samsung and many more PTZ protocol included
- Watermark Function
- Remote Observation Through Network
- Emergency Screen Auto Transfer to Center Software
- User friendly Graphic User Interface

### Outward Appearance



### Functions by Screen



WATCH SCREEN

PTZ SCREEN

SEARCH SCREEN

### Application

Some recommended installation areas are Security Companies, Change Booths, Casinos, Pawnshops, Jewelers, Galleries, Exhibition Halls, Department Stores, Convenience Stores, Discount Offices, Hospital, Police Stations, Subway Stations, Airports, Banks etc.

### Specifications

Model		KSR-816
Display	Speed	NTSC : 480fps PAL : 400fps
	Screen Division	1, 4, 9, 16 Division
Recording	Max. Speed (@CIF)	NTSC : 480fps PAL : 400fps
	Resolution	NTSC : 704×480, 704×240, 352×240 PAL : 704×576, 704×288, 352×288
	Recording Option	Continuous, Motion, Sensor, Pre-Alarm
Video	Format	NTSC/PAL
	CODEC	MPEG4
	Input	16ch
Audio	Output	VGA, CVBS, S-Video, Programmable spot out (1ch quad, 4ch full)
	CODEC	G. 726(8KHz Mono)
Alarm	Input	16 Ports
	Output	4 Ports
Network	Transmission	Ethernet (RJ45)
	Protocol	TCP/IP (support dynamic IP)
Backup	Device	USB, CD-RW, SCSI, IEEE1394, Network, DVD-RW (optional)
Other Function	Remote Control	Remote Software (CMS)
	Remote Alarm	E-mail, CMS report
	PTZ	RS232C/485
	W/D Function	Yes
	Image Authentication	Watermark
	Language	10 Languages
	Password	Multi-Level User Password Authorization
USB	1 Port (USB2.0)	
Working Temperature	0°C ~ +50°C	
Power Source	AC 100 ~ 240V, 50/60Hz	
Dimensions	400mm(W) × 100mm(H) × 458mm(D)	
Weight (net)	10.5Kg (23.1lbs)	

※ Please note 4channel and 8channel units will be available in the future  
※ Specifications subject to change without notice.

RECORDERS

CAMERAS

ACCESSORIES