

# Digital Video Recorder (Stand alone)

# LDV-S302 (4 channel)

New



## Feature

- Small File Sizes by MPEG-4 Compression
- Various Recording Resolution (704x480, 704x240, 352x240)
- Up to 120IPS @352 X 240 Recording
- Up to 800GB Internal Storage (Expandable if new high capacity HDD is launched)
- Default USB Mouse, IR Remote Controller
- User-Friendly GUI
- 4 Audio Channels
- Three USB 2.0 Ports
- Various Monitor Output
- Stable Embedded Linux Operating System
- File System Recovery of HDD After Power recovery by Journaling File System
- Multi-Languages Selectable
- Alarm Notification by e-Mail
- Pre-Alarm Recording
- Time and Date Sync from NTP Server
- Setup Configuration Export/Import
- Easy System S/W Update by USB Memory Stick and Network
- Multiplex (Simultaneous Live display, Recording, Search, Network, Back-up)
- Image Rate & Quality Adjustment per Individual Camera

## Rear View



## Specifications

Model		LDV-S302	
Video	Input	4	
	Output	Loop Through	4
		TV Out	1
		S-Video	1
		VGA	1
	Spot	1	
Audio	Input	4	
	Output	1(PB/Spot)	
Alarm	Input	4	
	Output	4	
	Pre-Alarm Recording	Up to 15min	
Recording	Image Rate (/Sec)	NTSC	Up to 120 IPS @ 352x240 Up to 60 IPS @ 704x240 Up to 30 IPS @ 704x480
		PAL	Up to 100 IPS @ 352x288 Up to 50 IPS @ 704x288 Up to 25 IPS @ 704x576
Display	Image Rate (/Sec)	NTSC	120 IPS (Real time per each channel)
		PAL	100 IPS (Real time per each channel)
Internal HDD	Max Capacity	800GB (Up to 2 HDDs)	
Backup	Backup Interface	USB 2.0, x 3 Network	
	Supportable Devices	Memory Stick CD-RW, HDD	
Others	PTZ Control Interface	RS-485 / RS-422, x 2	
	Serial Interface	RS-232C, x 2 (D-SUB9)	
	Network Connection	Ethernet 10/100M (RJ-45), PSTN	
Security	Password Protection	Yes	
	Image Authentication	Yes	
Power		AC Free 100~240V, 50/60Hz	
Dimension (WxDxH mm)		430 x 360 x 88	

## Dimension (unit : mm)

