

Speed Dome Camera

LPT-EP551PS (NTSC) LPT-EP553PS (PAL)

New



Feature

- Built in X27 Optical Zoom Lens
- 1/4" EX View CCD
- Day and Night function (I/R Cut Filter)
- Wide Dynamic Range (Dual Shutter)
- Digital Slow Shutter
- 128 Preset Position
- Auto focusing
- 0°~360°, Max 240°/Sec
- 0°~110°, Max 120°/Sec
- RS485 Communication

Specifications

Model	LPT-EP551PS	LPT-EP553PS
Signal System	NTSC	PAL
Total/Effective Pixels No	811(H) x 508(V) 410K	795 (H) X 596 (V) 470K
Pick-up Device	1/4" Ex View HAD CCD	
Lens	X27 Zoom (F 1.5 (W) ,F 3.8(T) f = 3.25 ~88.0 mm)	
Signal Process	Digital Signal Process	
Sync System	Internal	
Scanning Frequency(H)	15.734KHz	15.625KHz
Scanning Frequency(V)	59.94 Hz(VD)	50 Hz(VD)
Horizontal Resolution	500 Lines	
S/N Ratio	More Than 48dB (AGC Off)	
Standard Illuminance	Normal Mode : 1 Lux Night Mode : 0 Lux (IR on) / 0.005 Lux (IR off)	
Video Output Signal	1Vp-p Composite (75ohm)	
Wide Dynamic Range	Auto / Manual	
Electronic Sensitivity	Auto / Fix : x2, x3, x4,x20	
Control Method	RS485	
Iris Control	Auto / Manual	
Panning Range & Speed	0°~360°, Max 240°/Sec	
Tilting Range & Speed	0°~110°, Max 120°/Sec	
Auto Panning	2 point	
Preset	128 Position	
Pattern	5min	
Dome ID	256	
Alarm Input	8ch	
White Balance	Auto(ATW) / Indoor / Outdoor / Manual / Push Auto	
Power Source	AC 24V	
Power Consumption	Max13W	
Operation Temp	-10°C ~ 50°C ,0%RH~60%RH	
Storage Temp	-20°C ~ 60°C , 0%RH~85%RH	
Dimension(H x V x D)	ø230 x 300mm(H)	
Weight	3.3kg	

LPT-EP500 series : Pendant Mount Type

LPT-EW500 series : Wall Mount Type

LPT-EI500 series : Insert Type

Dimension (unit : mm)

