



---

## D/N 1080P AHD DOME IR Camera



---

### Features

- Video Output: AHD 1080P / AHD 720P / Analog 1280H
- AHD Cameras transmit data that is not encoded resulting in no process and no delay real time and complete transmission.
- Long transmission distance–Coaxial cable (3C/5C): 300M
- Seamless compatibility with the standard Analog equipment
- Automatically activates IR LED: Blow 10Lux
- High efficiency IR LED, radiant distance up to 16M
- “Up The Coax.” AHD camera supported

---

### Specifications

Model	AHD752A3.6
Resolution	1,920 (H) × 1,080 (V) @ 30 fps
Image Sensor/Sensor type	1/2.9" CMOS Image Sensor

Effective pixels	1,984 (H) x 1,105 (V)
Scanning System	Progressive Scan
Min. illumination/Low Light Mode (Colour)	0.03 Lux / F1.8, 0 Lux (IR On)
Lens	3.6mm
Iris	F2.0
Angle of View	(H)72.2° (V)52.9° (D)94.3°
Infrared LED Angle	30°
Max IR distance	16M
Peak wavelength	850nm
Sense Up	OFF / AUTO (X2 ~ X30)
Auto Gain Control	Auto (16 Steps)
White Balance	ATW / AWC / INDOOR / OUTDOOR / MANUAL / AWB
Shutter Time	Auto : 1/60(1/50)S ~ 1/50,000S ; Manual : 1/30(1/25)S, 1/60(1/50)S, FLK, 1/240S, 1/480S, 1/1,000S, 1/2,000S, 1/5,000S, 1/10,000S, 1/50,000S
3D Noise Reduction	2DNR & 3DNR
2D WDR	OFF / ON / AUTO
Privacy Masking	OFF / ON
S / N Ratio	More Than 55dB (AGC Off)
Video output	AHD 1080P / AHD 720P / 1280H
IR cut filter	Auto Selectable, Automatic Switch from Color Mode to Monochrome
Menu Control	OSD Control
Sync. Mode/ Synchronization	Internal
UTC	AHD-Coaxial protocol Supported
Back Light Compensation (BLC)	OFF / BLC / HSBLIC
Defog	OFF / AUTO
Privacy masking Zone	4 Zones
Languages	ENG / CHN1 / CHN2 / GER / FRA / ITA / SPA / POL / RUS / POR / NED / TUR / KOR / JPN / HEB / ARB
Operating temperature	- 10°C ~ + 50°C ( -14°F ~ 122°F )

---

Dimensions	φ93 x 74mm (H)
Weight	230g
Power Supply	DC12V ±10%
Power Consumption	3W

---