



CMR352X

- High efficiency IR LED , 30M
- Innovatory external adjustment with waterproof for zoom and focus of Vari-Focal lens
- Aluminum housing with IP66 rating
- Perfect Solution for Day/Night Applications



# *Vandal & Water Proof*

*D/n Vandal Resistant Vari-focal  
IR Dome Camera*






## CMR352X



### Features

- High Efficiency IR LED(Ø5\*35Pcs); Radiant Distance 30M
- Aluminum Housing with IP66 Rating
- Housing and Bottom Chassis are Integrated
- Innovatory External Adjustment with Waterproof for Zoom and Focus of Vari-Focal Lens
- Impact Resistant Polycarbonate Transparence Mask
- Infrared Cut Filter Mechanism, Auto Color & Mono Switching
- Automatically Activates IR LED: Below 10Lux



### Specifications

D/N VANDAL RESISTANT VARI-FOCAL IR DOME CAMERA		
Model No	CMR352X3.6N	CMR352X3.6P
Lens	Focal Length	3.3~12mm
	Iris	F1.4
	Angle of view	H
V		63.6° ~ 17.9°
D		125.7° ~ 29.9°
Power Input Voltage	DC12V±10%	
System	NTSC or PAL	
Sync. Mode	Internal	
Pick Up Element	1/3" Super HAD CCD Sensor	
Effective Pixels	768(H) x 494(V) [NTSC]	752(H) x 582(V) [PAL]
Chip Size	5.59mm(H) x 4.68mm(V)	
Horizontal & Vertical Sync. Frequency	15.734KHz / 59.94Hz [NTSC]	15.625KHz / 50Hz [PAL]
Scanning System	2 : 1 Interlace	
Infrared Cut Filter	Auto Selectable, Automatic Switch From Color Mode to Monochrome	
Resolution	Color: 540TV Lines, Mono: 600TV Lines	
Minimum Illumination	Color: 0.05Lux / F1.4, Mono: 0.01Lux / F1.4, 0Lux(IR ON)	
S/N Ratio	More Than 50dB (AGC OFF)	
Auto Gain Control	36dB Variable Gain	
White Balance	ATW	
Aperture Correction	Horizontal, Vertical	
Power Consumption	6.8W	
Back Light Compensation	Auto	
Video Output	CVBS1.0Vp-p , 75Ohm	
Operating Temperature	-10°C ~ +50°C (14°F ~ 122°F)	
Gamma Characteristic	γ= 0.45	
IP Rating	IP66	
Vandal Proof	Withstand a blow from a 10 lbs sledgehammer	
Infrared LED	Peak Wavelength	850nm
	Beam Spread	30°
	Radiant Distance	30M
Dimension	Ø130 x 110mm	
Weight	880g	

Design and specifications are subject to change without notice.