

## PIH 931D/932T/800III/800EK



PIH-932T



PIH-931D

### Specifications

#### ⊕ Multifunction 3D/2D Keyboard Controller

Model No.	PIH-931D	PIH-932T
Joystick	3 Axis (Pan/ Tilt/ Zoom)	2 Axis (Pan/ Tilt)
Movement Speed control	Pan 8 Steps Tilt 8 Steps Zoom 16 Steps	Pan 8 Steps Tilt 8 Steps
Data Communication	RS-485 Standard(Format N, 8, 1, Baud rate 9600bps)	
Connector	RJ-45 / 8Pin	
Control Mode	PTZ / MATRIX / DVR	
LCD Display	20 Characters x 4 Lines	
Keyboard Keypad	Total 54 keys 0~9 Numeric keys	
Input Voltage	DC 12V 10% / 250mA	
Power Consumption	3W	
Operating Temperature	-5°C ~ + 60°C (23°F ~140°F)	
Dimension	340(W) x 194(D) x 103(H) mm	
Weight	1350 g	1300 g

### Specifications

#### ⊕ Keyboard Controller

Model	PIH-800III
Input Voltage	12Vdc
DIP Switch Setting	Direct to Dome / Master/ Slave
Telemetry Output	1 x RS-485
Telemetry Input	1 x RS-485
RS-485 Max Distance	1000m



### Specifications

#### ⊕ Keyboard Expander

Model	PIH-800EK
Input Voltage	DC12V
Power Consumption	250mA
Control Interface	RS-485( 1 Input / 1 Output)
Baud Rate	9600,N,8,1
LED Indicator	Green: Power, Red: Transmission, Yellow: Receiving
Connection Capacity	Keyboard Controller: 4, Fast Dome Camera: 64
Diameter(mm)	92(L) x 73(W) x 27(H)
Weight	60g

