

PIH 5480/5880/5480M/5880M/54200/58200



LILIN



PIH-54200/58200



PIH-5480/5880

PIH-5480M/5880M

## Specifications

### ⊕ Infrared Illuminator Housing

Model No.	PRH-5480	PRH-5880	PRH-5480M	PRH-5880M	PRH-54200	PRH-58200
Power Input Voltage	AC24V ± 10%	AC90 ~ 260V max.	AC24V ± 10%	AC90 ~ 260V max.	AC24V ± 10%	AC90 ~ 260V max.
Radiant Distance	100m		60m		200m	
Window	Φ110 Heat Resistant Glass					
Glass Thickness	3mm					
Infrared LED	Wave Length					
	850nm					
	Angle		10° + 30°		30°	
	Quantity		11 units (10°) + 6 units (30°)		17 units	
Power On		Sensor Auto Control, Adjustable Control Point			5 units (6°) + 2 units (30°)	
Blower Control		On: 35°C Off: 25°C				
Heater Control		On: 15°C Off: 25°C				
Suitable Camera and Lens		Max. 200mm length				
IP Rating		IP66				
Mounting		Bottom				
Construction		Aluminum				
Power Consumption		22W			32W	
Operating Temperature		-20°C ~ +60°C (-4°F ~ +140°F)				
Dimension		Housing : Φ134 x 318mm (L), Bracket : 205mm (L)			Housing : Φ134 x 318mm (L), Bracket : 211.5mm (L)	
Weight		3500g				

