

S8D4654EX25

25X 5MP Day & Night 30 FPS
Vandal Resistant PTZ IP Camera

S8D
SERIES

Speeddome PTZ cameras offer advanced optical zoom capabilities and physical PTZ (Pan-Tilt-Zoom) functions, providing exceptional flexibility in adjusting viewing angles and zoom levels.

5MP

ONVIF® | S T G

- 25X Optical Zoom Lens(5.3 – 132.5mm)
- 8X Digital Zoom
- Day & Night (IR cut removable)
- 5 megapixel CMOS image sensor
- 5MP H.265/HEVC and H.264/AVC high-performance video compression
- Simultaneous streaming of H.265 and H.264 encoded streams
- 3D noise reduction (MCTF)
- HDR function up to 120dB
- IVS supported
- Motion / Tamper / Audio / Alarm / Network lost detection / Global Counter / Virtual Input / Metadata function
- SMART event
- Defog function
- Dynamic privacy zone mask
- Horizontal & Vertical Flip
- 360° Endless panning
- Tilting range up to 192 °
- Up to 256 Programmable Preset Positions
- 2-way audio supported
- ONVIF supported
- RS-485 supported
- Weatherproof IP66
- Vandal resistant approve IK10



Video Performance	
Min. Illumination	0.04 lux (1/30 sec, F1.6(Wide), 30IRE, AGC-Gain: 60dB ICR-OFF Color mode) 0.008 lux (1/30 sec, F1.6(Wide), 30IRE, AGC-Gain: 60dB ICR-ON B/W mode) 0.008 lux (1/8 sec, F1.6(Wide), 30IRE, AGC-Gain: 60dB ICR-OFF Color mode) 0.001 lux (1/8 sec, F1.6(Wide), 30IRE, AGC-Gain: 60dB ICR-ON B/W mode)
Lens / Night vision (infrared LED)	
Lens zoom ratio	25X Optical
Focal Length	5.3 (WIDE) – 132.5 (TELE) mm
Minimum Aperture Ratio	F1.6(Wide) – F4.3(Tele)
Iris Range	F1.6 – 32 , Close
Iris Control	DC IRIS , ALC (Adjustable Output Target Level) / Manual
Minimum Object Distance	50 cm (WIDE end), 1.5M (TELE end)
Angle of View	56.7° (W) – 3.2° (T) (H) 42.9° (W) – 2.6° (T) (V) 70.2° (W) – 2.0° (T) (D)
Zoom Speed	0 – 7 Selectable [Fast : Approx. 6.0 Second (Tele to Wide) in Manual Mode]
Focus Speed	0 – 7 Selectable
Focus	Auto (Continue / Interval / Zoom Trigger / One Push), Manual Focus
Sensor	
Pick Up Element	1/2.8" CMOS image sensor
Effective Pixels	2616 (H) × 1964 (V) = 5,137,824 (Pixels)
Certifications	
CE	Yes, EMI Class A
FCC	Yes, EMI Class A
IP Rating	IP66
Vandal Resistant Rating	IK10 (Housing)
Pan & Tilt	
Control Function	Pan and Tilt / Zoom and Focus / Iris and ICR / 256 Preset Position / Home Position
Auto Mode	OFF / SCAN(16) / SEQ(256) / TOUR(16) / PATROL(16) / Auto TRACKING
Schedule Setting	OFF / SCAN (4)/ SEQ(256) / TOUR(4) / PATROL(4) / Preset Position(256)(via web interface)
Panning range	360° Endless
Panning mode	Manual , Auto , Manual Position , Sequential Position
Panning speed	Manual Approx. 0.1° /s – 120° /s 8 Steps, Preset Approx. 1° /s – 360° /s, Alarm Trigger Speed 360° /s
Tilting range	-6° – +186°
Tilting mode	Manual , Auto , Manual Position , Sequential Position
Tilting speed	Manual Approx. 0.1° /s – 120° /s 8 Steps, Preset Approx. 1° /s – 360° /s, Alarm Trigger Speed 360° /s
PC Requirements	
CPU	Intel® Core™ i7 or higher grade
OS	Windows 7 or above
RAM	8GB or above, Dedicated Graphics Card
Web browser	Microsoft® Internet Explorer® 9 or above

Input / Output	
Audio Input / Output	one audio input / one audio output Terminal block type (microphone not built- in)
Live Video Output	CVBS 1.0Vp-p, 75 ohm, BNC connector
Audio	Two-way Audio, G.711 u-law / PCM / AAC, External Microphone Required
Alarm Input / Output	Digital 4 Input (TTL 5Vdc) , 2 Output (MOS Relay contact N.O., Load.max. 40VDC,450mW / 300mA,450mW) , Terminal block type
Video Streaming	
Video Compression	H.265/HEVC main profile, H.264 main and high profile , Motion JPEG
Video Streaming	RTP/HTTP, RTP/TCP, RTP/UDP, Multicast streams in H.265 and H.264 and Motion JPEG, configurable frame rate and bandwidth
Video Bitrate	128Kbps – 12Mbps; Frame rate and bit rate controllable on-the-fly; VBR / CBR / GOP supported, Fixed bitrate,
Network Security	
Encryption	Base64 HTTP encryption, HTTPS encryption
Authentication	Digest HTTP authentication, RTSP authentication, DDNS via HTTPS
Address Filter	Yes
Access	Multiple user access levels with password protection
Users	10 user accounts available
Multi IP address	Yes
Video Resolutions (H x V)	
Resolution	5MP(2592 × 1944), 4MP(2304 × 1728), 3.1MP(2048 × 1536), 3MP(2304 × 1296), 2MP(1920 × 1080), 1.3MP(1280 × 960), 1MP(1280 × 720), D1(720 × 480, 720 × 576), VGA(640 × 480), CIF(352 × 240)
Maximum Frame Rate	Normal mode: 60Hz: 30 FPS @ 2592 × 1944 50Hz: 25 FPS @ 2592 × 1944 HDR mode: 60Hz: 30 FPS @ 2592 × 1944 50Hz: 25 FPS @ 2592 × 1944
Video Functions	
Scanning System	Progressive Scan
Infrared Cut Filter	Auto / Day (Color) / Night (Mono) / Schedule
White Balance	Auto / Manual
Electrical Shutter	1/30(1/25)s – 1/20000s
Exposure Mode	AUTO / SHUT.P / IRIS.P
Sense Up	Off / x2 / x4 / x8
Sense Up+	Yes
Auto Gain Control	60 dB Variable Gain
S/N Ratio	More than 50dB (AGC off)
3D Noise Reduction	Off / ON(1 – 32)
High Dynamic Range	Up to 120dB (by HDR mode, 2 shutter line interleave)
Privacy Masking	OFF / ON (Up to 16 area)
Image Effects	Brightness, Contrast, Hue, Saturation, Sharpness, Mirror, Flip, Defog, Digital Zoom(x8)

Integration	
Mobile Application	Integrated to LILIN mobile app (LILIN Pro) iPhone, iPad, Android support
Video Management	ONVIF Profile S / ONVIF Profile T / ONVIF Profile G, IVS events, LILIN Navigator Enterprise 3.0 support, Third party VMS through LILIN HTTP API
SD Card Recording	Support (128GB) Micro SD/SDHC/SDXC card for circular recording (card is not included)
SD Card Compatible List	Micron - 32GB,64GB,128GB,256GB,512GB, 1TB (SDXC, U1, C10) Transcend - 4GB SD,8GB SDHC,32GB SDHC C10,128GB SDXC C10 SanDisk - 8GB SDHC, 32GB, 64GB, 128GB SDHC C10 Kingston - 64GB SDXC C10
Maintenance	Firmware update via HTTP and IP Scan; Firmware available at website
IVS Basic 1.0	Motion / Tamper
Event Triggers	Motion / Tamper / Audio / Alarm / Network lost detection / Global Counter / Virtual Input / Metadata
Event actions	FTP / SMTP / HTTP post / SD card / SAMBA / Alarm Output / Push Service / Global Counter / Virtual Input
Control Interface	RS-485, Half-Duplex, support MLP2, Pelco D/P protocols
Languages	English, Traditional Chinese, Simplified Chinese, Russian, Italian, Hungarian, Korean, French, Turkish, Arabic, Spanish, Japanese
Power and Environment	
Ethernet	10/100 Mbps Base-T, RJ-45
ePTZ & Digital Zoom	- / Yes (X8)
Web PTZ control	Pan , tilt , zoom in / out , absolute position, and video-click-n-move
OSD	Position configurable text overlay for date, time, camera ID, event status/ Current PTZ Position/ Preset Name, Auto-Pan
CPU, Memory	Embedded Quad-core ARM Cortex-A53 1.0GHz CPU & 1GB LPDDR4X, 8GB e.MMC memory
OS	Embedded Linux 4.9.84
Network Protocols	IPv4, TCP, UDP, HTTP, HTTPS, QoS, NTP, DDNS, FTP, ARP, DHCP, PPPoE, DNS, RTSP, RTCP, Telnet, ICMP, ONVIF Profile S, ONVIF Profile T, ONVIF Profile G
Network Storage	NAS (Support SAMBA/CIFS)
User accounts	10 user accounts available
Video Display	LILIN Universal ActiveX & HTML5

Power and Environment	
Starting Temperature	- 40° C – + 50° C (-40° F – 122° F)
Operating Temperature	- 40° C – + 50° C (-40° F – 122° F)
Storage Temperature	- 20° C – + 60° C (-4° F – 160° F)
Humidity	0% – 90%
Power Supply	AC24V ±10% / DC24V / PoE++ (IEEE 802.3bt)
Power Consumption	AC24V, 20.1 W / DC24V, 20.8 W / PoE++, 19.8 W (Heater OFF) AC24V, 31.2 W / DC24V, 32.6 W / PoE++, 33.0 W (Heater ON)
Mechanical	
Dimension	275 (H) × 192 (D) mm
Weight	3100 g
Casing Material	Aluminum alloy
Window	Transparent dome cover
Warranty	
Warranty	3 Year(s)

Bracket



BTS03W

Wall-mount

Bracket



BTS06W

Wall-mount

Bracket



PIH-5208HBW

Wall-mount

Bracket



PIH-5208LBW

Wall-mount

Bracket



PIH-520HBW

Wall-mount

Bracket



PIH-520LBW

Wall-mount

Bracket



PIH-520LW

Wall-mount