



- Quick-Install Mounting Ring
- Local BNC Test Loop
- High Performance 540TVL
- Cost Effective
- 2.8-11mm Varifocal Lens

## D3P Series Indoor Domes

The D3P Series are indoor, plastic domes that offer high quality performance at economical prices. Designed with the installer in mind, the dome's base detaches for easy mounting. Color Hi-Res, True Day Night, and Pixim™ Wide Dynamic Range versions are available.

### Specifications

D3P Series	Model D3PDN211	Model D3PCH211	Model D3PWD211
	True Day/Night Camera	Color Hi-Res Camera	Wide Dynamic Range Camera
Imager	1/3" Sony Super HAD II CCD	1/3" Sony CCD	1/3" Pixim DPS Sensor
Signal System	NTSC		
Effective Pixels	768 (H) x 494 (V)		720 (H) x 480 (V)
Resolution	540TVL		
Minimum Illumination	0.3Lux/F1.2 (Color) 0.008Lux/F1.2 (B/W)	0.1Lux/F1.2	0.5Lux/F1.2; 0.08Lux/F1.2 (Slow Shutter)
S/N Ratio	>50dB (AGC Off)	>50dB	>50dB
Dynamic Range	-	-	101dB Typical, 120dB Max
Control Method	-	-	OSD + Dipswitch
Privacy Masking	-	-	12 zones (optional)
Day/Night Function	Mechanical IR Cut Filter	-	Electronic D/N
Lens	2.8-11mm Auto-Iris		
White Balance	Auto		AWB/ATW/Manual Selectable
AWB Range	-	-	ATW 2,000K to 11,000K
BLC	Auto		-
AGC	Auto		Adjustable
Gamma Correction	-	-	Adjustable
Sync Mode	Internal		Internal / Line Lock
Video Output	1.0Vp-p, 75 Ohm		0.8-1.5Vp-p adjustable, 75 Ohm
Power Supply	12VDC/24VAC		
Power Consumption	<4W	<3.5W	<3W
Dimensions (Dome)	3.75" (95mm) Diameter		
Dimensions (Whole Unit)	5.92" (150mm) Width, 4.3" (109mm) Height		

#### Accessory Item - UTP Converter (-U)

Note: Part numbers ending in "E" do not include a test loop.



1950 Camino Vida Roble, Suite 150  
Carlsbad, CA 92008  
Tel: 760.438.7000 800.421.1587  
[www.aigismech.com](http://www.aigismech.com) • [www.linearcorp.com](http://www.linearcorp.com)