

Day/night analog outdoor dome camera 700TVL

LTV-CDH-821LHW-V2.8-12



- 600/650 TV lines resolution
- Day and Night : Auto (ICR), Color & B/W
- 2.8-12 mm varifocal lens
- IR illumination 30 m
- System Noise Reduction 2D-DNR+3D-DNR
- Extended dynamic range WDR
- Sens-up (x512)
- Functions ALC, BLC, AGC, D-Zoom
- Dual power 12B (DC) / 24B (AC)
- Vandal resistant
- Operating Temperature -45°C...+50°C

Video	Imaging device	1/3" Sony Super HAD II Double Scan CCD
	Total Pixels	795x596
	Effective Pixels	752x582
	Electronic shutter speed	1/50-1/10 000 c
	Resolution	600/650 TV lines resolution
	Video Min illumination	Colour : 0.1Lux@F1.2; B/W : 0.01Lux@F1.2; Sens-up : 0.0004Lux@F1.2; B/W : 0Lux (IR LED On)
	Video Output	1.0 Vp-p / 75 Ω composite
	Gamma Correction	0,45
	Synchronisation	Internal
	S-N Ratio	52dB (AGC off), 54dB (WDR on)
Lens	Lens Type	Vario
	Focal Length zoom ratio	2.8 - 12mm
	iris Control	DD
Functions	Day and Night	Auto (ICR) / Colour / B/W
	IR illumination	30 m
	Backlight Compensation	ALC, BLC
	Gain control	AGC
	White Balance	AWB
	Digital Noise Reduction	2D-DNR + 3D-DNR
	Sens-up frame integration	Sens-up (x512)
	Contrast Enhancement	WDR (54dB)
	Motion Detection	4 programmable zones
	Privacy Masking	8 programmable zones
	OSD menu	Yes
	Heater	Yes
	Physical parameters	Input Voltage -Current
Operating Temperature		-45°C...+50°C
Dimensions WxHxD		149x139.6 mm
Weight		950 g