

SMART LINE

Wi-Fi Outdoor Mini Dome Camera

LTV CND-820 C2

Article No.: 22600006



Main Features:

- H.264 & MJPEG dual-stream encoding
- Max. 20fps@3M (2304 x 1296) and 25/30fps@1080P (1920 x 1080)
- Day/Night
- 3.6 mm fixed lens
- Wi-Fi
- IP67, IK10
- 12V DC



Accessories:

Picture	Article No.	Model Name
	41000026	LTV-BMW-50-SD

Camera		
Image Sensor	1/3" 3 Megapixel progressive scan CMOS	
Effective Pixels	2304 x 1536	
Electronic Shutter Speed	Auto/Manual 1/3(4) ~ 1/100000s	
Min. Illumination	Color: 0.01Lux/F2.0; IR on: 0Lux/F2.0	
S/N Ratio	More than 50dB	
Lens		
Focal Length	3.6mm	
Lens Type	Fixed lens	
FOV	77°	
Video		
Compression	H.264/H.264H/H.264B/MJPEG	
Resolution	3M (2304x1296) / 1080P (1920x1080) / 720P (1280x720) / VGA (640x480) / QVGA (320x240)	
Frame Rate	Main Stream	3M (1 ~ 20fps) / 1080P (1 ~ 25/30fps)
	Sub Stream	VGA (1 ~ 25/30fps)
Bitrate	H.264: 32kbps ~ 8192kbps	
Function		
IR Lights	Max. 30m	
Day/Night	Auto (ICR), color, B/W	
Backlight Compensation	BLC / HLC / DWDR	
White Balance	Auto/manual	
Gain Control	Auto/manual	
Noise Reduction	3D	
Privacy Masking	Up to 4 areas	
Network		
Ethernet	RJ-45 (10/100Base-T)	
Wi-Fi	Wi-Fi (802.11b/g/n)	
Protocols	IPv4/IPv6, HTTP, HTTPS, TCP/IP, UDP, UPnP, ICMP, IGMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPoE, DDNS, FTP, IP Filter, QoS	
Compatibility	ONVIF, CGI	
Smartphone	iPhone, iPad, Android, Windows Phone	
Miscellaneous		
Power Supply	12V DC	
Power Consumption	<5.5W	
Operating Temperature	-30°C ... +50°C, less than 95% RH	
Protection Class	IP67	
Dimensions	Ø 110 x 81 mm	
Weight	0.55kg	